NAPA

Sales Brochure
售樓説明書



NAPA

NOTES TO PURCHASERS OF FIRST-HAND RESIDENTIAL PROPERTIES
一手住宅物業買家須知

You are advised to take the following steps before purchasing first-hand residential properties.

For all first-hand residential properties

1. Important information

- Make reference to the materials available on the Sales of First-hand Residential Properties Electronic Platform (SRPE) (www.srpe.gov.hk) on the first-hand residential property market.
- Study the information on the website designated by the vendor for the development, including the sales brochure, price lists, documents containing the sales arrangements, and the register of transactions of a development.
- Sales brochure for a development will be made available to the general public at least 7 days immediately before a date of sale while price list and sales arrangements will be made available at least 3 days immediately before the date of sale.
- Information on transactions can be found on the register of transactions on the website designated by the vendor for the development and the SRPE.

2. Fees, mortgage loan and property price

- Calculate the total expenses of the purchase, such as solicitors' fees, mortgage charges, insurance fees and stamp duties.
- Check with banks to find out if you will be able to obtain the needed mortgage loan, select the appropriate payment method and calculate the amount of the mortgage loan to ensure it is within your repayment ability.
- Check recent transaction prices of comparable properties for comparison.
- Check with the vendor or the estate agent the estimated management fee, the amount of management fee payable in advance (if any), special fund payable (if any), the amount of reimbursement of the deposits for water, electricity and gas (if any), and/or the amount of debris removal fee (if any) you have to pay to the vendor or the manager of the development.

3. Price list, payment terms and other financial incentives

- Vendors may not offer to sell all the residential properties that are covered in a price list. To know which residential properties the vendors may offer to sell, pay attention to the sales arrangements which will be announced by the vendors at least 3 days before the relevant residential properties are offered to be sold.
- Pay attention to the terms of payment as set out in a price list. If there are discounts on the price, gift, or any financial advantage or benefit to be made available in connection with the purchase of the residential properties, such information will also be set out in the price list.
- If you intend to opt for any mortgage loan plans offered by financial institutions specified by the vendor, before entering into a preliminary agreement for sale and purchase (PASP), you must study the details of various mortgage loan plans[1] as set out in the price list concerned. If you have any questions about these mortgage loan plans, you should check with the financial institutions concerned direct before entering into a PASP.

4. Property area and its surroundings

- Pay attention to the area information in the sales brochure and price list, and price per square foot/metre in the price list. According to the Residential Properties (First-hand Sales) Ordinance (Cap. 621) (the Ordinance), vendors can only present the area and price per square foot and per square metre of a residential property using saleable area. Saleable area, in relation to a residential property, means the floor area of the residential property, and includes the floor area of every one of the following to the extent that it forms part of the residential property - (i) a balcony; (ii) a utility platform; and (iii) a verandah. The saleable area excludes the area of the following which forms part of the residential property - air-conditioning plant room; bay window; cockloft; flat roof; garden; parking space; roof; stairhood; terrace and yard.
- Floor plans of all residential properties in the development have to be shown in the sales brochure. In a sales brochure, floor plans of residential properties in the development must state the external and internal dimensions of each residential property[2]. The external and internal dimensions of residential properties as provided in the sales brochure exclude plaster and finishes. You are advised to note this if you want to buy furniture before handing over of the residential property.
- Visit the development site and get to know the surroundings of the property (including transportation and community facilities). Check town planning proposals and decisions which may affect the property. Take a look at the location plan, aerial photograph, outline zoning plan and cross-section plan that are provided in the sales brochure.

5. Sales brochure

- Ensure that the sales brochure you have obtained is the latest version. According to the Ordinance, the sales brochure made available to the public should be printed or examined, or examined and revised within the previous 3 months.
- Read through the sales brochure and in particular, check the following information in the sales brochure -
  - whether there is a section on "relevant information" in the sales brochure, under which information on any matter that is known to the vendor but is not known to the general public, and is likely to materially affect the enjoyment of a residential property will be set out. Please note that information contained in a document that has been registered with the Land Registry will not be regarded as "relevant information";
  - the cross-section plan showing a cross-section of the building in relation to every street adjacent to the building, and the level of every such street in relation to a known datum and to the level of the lowest residential floor of the building. This will help you

[1] The details of various mortgage loan plans include the requirements for mortgagors on minimum income level, the loan limit under the first mortgage and second mortgage, the maximum loan repayment period, the change of mortgage interest rate throughout the entire repayment period, and the payment of administrative fees.

[2] According to section 10(2)(d) in Part 1 of Schedule 1 to the Ordinance, each of the floor plans of the residential properties in the development in the sales brochure must state the following—
(i) the external dimensions of each residential property;
(ii) the internal dimensions of each residential property;
(iii) the thickness of the internal partitions of each residential property;
(iv) the external dimensions of individual compartments in each residential property.
According to section 10(3) in Part 1 of Schedule 1 to the Ordinance, if any information required by section 10(2)(d) in Part 1 of Schedule 1 to the Ordinance is provided in the approved building plans for the development, a floor plan must state the information as so provided.

visualize the difference in height between the lowest residential floor of a building and the street level, regardless of how that lowest residential floor is named;

- interior and exterior fittings and finishes and appliances;

- the basis on which management fees are shared;

- whether individual owners have obligations or need to share the expenses for managing, operating and maintaining the public open space or public facilities inside or outside the development, and the location of the public open space or public facilities; and

- whether individual owners have responsibility to maintain slopes.

6. Government land grant and deed of mutual covenant (DMC)

- Read the Government land grant and the DMC (or the draft DMC). Information such as ownership of the rooftop and external walls can be found in the DMC. The vendor will provide copies of the Government land grant and the DMC (or the draft DMC) at the place where the sale is to take place for free inspection by prospective purchasers.

- Check the Government land grant on whether individual owners are liable to pay Government rent.

- Check the DMC on whether animals can be kept in the residential property.

7. Information on Availability of Residential Properties for Selection at Sales Office

- Check with the vendor which residential properties are available for selection. If a "consumption table" is displayed by the vendor at the sales office, you may check from the table information on the progress of sale on a date of sale, including which residential properties are offered for sale at the beginning of that date of sale and which of them have been selected and sold during that date of sale.

- Do not believe in rumours about the sales condition of the development and enter into a PASP rashly.

8. Register of Transactions

- Pay attention to the register of transactions for a development. A vendor must, within 24 hours after entering into a PASP with a purchaser, enter transaction information of the PASP in the register of transactions. The vendor must, within 1 working day after entering into an agreement for sale and purchase (ASP), enter transaction information of the ASP in the register of transactions. Check the register of transactions for the concerned development to learn more about the sales condition of the development.

- Never take the number of registrations of intent or cashier orders a vendor has received for the purpose of registration as an indicator of the sales volume of a development. The register of transactions for a development is the most reliable source of information from which members of the public can grasp the daily sales condition of the development.

9. Agreement for sale and purchase

- Ensure that the PASP and ASP include the mandatory provisions as required by the Ordinance.

- Pay attention that fittings, finishes and appliances to be included in the sale and purchase of the property are inserted in the PASP and ASP.

- Pay attention to the area plan annexed to the ASP which shows the total area which the vendor is selling to you. The total area which the vendor is selling to you is normally greater than the saleable area of the property.

- A preliminary deposit of **5%** of the purchase price is payable by you to the owner (i.e. the seller) on entering into a PASP.

- If you do not execute the ASP within **5 working days** (working day means a day that is not a general holiday or a Saturday or a black rainstorm warning day or gale warning day) after entering into the PASP, the PASP is terminated, the preliminary deposit (i.e. 5% of the purchase price) is forfeited, and the owner (i.e. the seller) does not have any further claim against you for not executing the ASP.

- If you execute the ASP within 5 working days after the signing of the PASP, the owner (i.e. the seller) must execute the ASP within 8 working days after entering into the PASP.

- The deposit should be made payable to the solicitors' firm responsible for stakeholding purchasers' payments for the property.

10. Expression of intent of purchasing a residential property

- Note that vendors (including their authorized representative(s)) should not seek or accept any specific or general expression of intent of purchasing any residential property before the relevant price lists for such properties are made available to the public. You therefore should not make such an offer to the vendors or their authorized representative(s).

- Note that vendors (including their authorized representative(s)) should not seek or accept any specific expression of intent of purchasing a particular residential property before the sale of the property has commenced. You therefore should not make such an offer to the vendors or their authorized representative(s).

11. Appointment of estate agent

- Note that if the vendor has appointed one or more than one estate agents to act in the sale of any specified residential property in the development, the price list for the development must set out the name of all the estate agents so appointed as at the date of printing of the price list.

- You may appoint any estate agent (not necessarily from those estate agency companies appointed by the vendor) to act in the purchase of any specified residential property in the development, and may also not appoint any estate agent to act on your behalf.

- Before you appoint an estate agent to look for a property, you should -

  - find out whether the agent will act on your behalf only. If the agent also acts for the vendor, he/she may not be able to protect your best interests in the event of a conflict of interest;

  - find out whether any commission is payable by you to the estate agent and, if so, its amount and the time of payment; and

  - note that only licensed estate agents or salespersons may accept your appointment. If in doubt, you should request the estate agent or salesperson to produce his/her Estate Agent Card, or check the Licence List on the Estate Agents Authority website: www.eaa.org.hk.

12. Appointment of solicitor

- Consider appointing your own solicitor to protect your interests. If the solicitor also acts for the vendor, he/she may not be able to protect your best interests in the event of a conflict of interest.

- Compare the charges of different solicitors.

For first-hand uncompleted residential properties

13. Pre-sale Consent

- For uncompleted residential property under the Lands Department Consent Scheme, seek confirmation from the vendor whether the "Pre-sale Consent" has been issued by the Lands Department for the development.

14. Show flats

- While the vendor is not required to make any show flat available for viewing by prospective purchasers or the general public, if the vendor wishes to make available show flats of a specified residential property, the vendor must first of all make available an unmodified show flat of that residential property and that, having made available such unmodified show flat, the vendor may then make available a modified show flat of that residential property. In this connection, the vendor is allowed to make available more than one modified show flat of that residential property.

- If you visit the show flats, you should always look at the unmodified show flats for comparison with the modified show flats. That said, the Ordinance does not restrict the discretion of the vendor in arranging the sequence of the viewing of unmodified and modified show flats.

- Sales brochure of the development should have been made available to the public when the show flat is made available for viewing. You are advised to get a copy of the sales brochure and make reference to it when viewing the show flats.

- You may take measurements in modified and unmodified show flats, and take photographs or make video recordings of unmodified show flats, subject to reasonable restriction(s) which may be set by the vendor for ensuring safety of the persons viewing the show flat.

For first-hand uncompleted residential properties and completed residential properties pending compliance

15. Estimated material date and handing over date

- Check the estimated material date[3] for the development in the sales brochure.

  - The estimated material date for a development in the sales brochure is not the same as the date on which a residential property is handed over to purchaser. The latter is inevitably later than the former.

- Handing over date

  - The mandatory provisions to be incorporated in an ASP as required by the Ordinance include a provision requiring the vendor to apply in writing for an Occupation Document/a Certificate of Compliance or the Director of Lands' Consent to Assign (as the case may be) in respect of the development within 14 days after the estimated material date as stipulated in the ASP.

    - ➢ For development subject to the Lands Department Consent Scheme, the vendor is required to notify the purchaser in writing that the vendor is in a position validly to assign the property within one month after the issue of the Certificate of Compliance or the Consent to Assign, whichever first happens; or

    - ➢ For development not subject to the Lands Department Consent Scheme, the vendor is required to notify the purchaser in writing that the vendor is in a position validly to assign the property within 6 months after the issue of the Occupation Document including Occupation Permit.

  - The mandatory provisions to be incorporated in an ASP as required by the Ordinance include a provision requiring completion of the sale and purchase within 14 days after the date of the notification aforesaid. Upon completion, the vendor shall arrange handover of the property to the purchaser.

- Authorized Person (AP) may grant extension(s) of time for completion of the development beyond the estimated material date.

  - The mandatory provisions to be incorporated in an ASP as required by the Ordinance include a provision that the AP of a development may grant an extension of time for completion of the development beyond the estimated material date having regard to delays caused exclusively by any one or more of the following reasons:

    - ➢ strike or lock-out of workmen;

    - ➢ riots or civil commotion;

    - ➢ force majeure or Act of God;

    - ➢ fire or other accident beyond the vendor's control;

    - ➢ war; or

    - ➢ inclement weather.

  - The AP may grant more than once such an extension of time depending on the circumstances. That means handover of the property may be delayed.

  - The mandatory provisions to be incorporated in an ASP as required by the Ordinance also include a provision requiring the vendor to, within 14 days after the issue of an extension of time granted by the AP, furnish the purchaser with a copy of the relevant certificate of extension.

- Ask the vendor if there are any questions on handing over date.

For first-hand completed residential properties

16. Vendor's information form

- Ensure that you obtain the "vendor's information form(s)" printed within the previous 3 months in relation to the residential property/properties you intend to purchase.

[3] Generally speaking, "material date" means the date on which the conditions of the land grant are complied with in respect of the development, or the date on which the development is completed in all respects in compliance with the approved building plans or the conditions subject to which the certificate of exemption is issued. For details, please refer to section 2 of the Ordinance.

17. Viewing of property

- Ensure that, before you purchase a residential property, you are arranged to view the residential property that you would like to purchase or, if it is not reasonably practicable to view the property in question, a comparable property in the development, unless you agree in writing that the vendor is not required to arrange such a comparable property for viewing for you. You are advised to think carefully before signing any waiver.

- You may take measurements, take photographs or make video recordings of the property, unless the property is held under a tenancy or reasonable restriction(s) is/are needed to ensure safety of the persons viewing the property.

For complaints and enquiries relating to the sales of first-hand residential properties by the vendors which the Ordinance applies, please contact the Sales of First-hand Residential Properties Authority -

Website	: www.srpa.gov.hk
Telephone	: 2817 3313
Email	: enquiry_srpa@hd.gov.hk
Fax	: 2219 2220

Other useful contacts:

Consumer Council	
Website	: www.consumer.org.hk
Telephone	: 2929 2222
Email	: cc@consumer.org.hk
Fax	: 2856 3611
Estate Agents Authority	
Website	: www.eaa.org.hk
Telephone	: 2111 2777
Email	: enquiry@eaa.org.hk
Fax	: 2598 9596
Real Estate Developers Association of Hong Kong	
Telephone	: 2826 0111
Fax	: 2845 2521

Sales of First-hand Residential Properties Authority
Transport and Housing Bureau
August 2017

您在購置一手住宅物業之前，應留意下列事項：

適用於所有一手住宅物業

1. 重要資訊

- 瀏覽一手住宅物業銷售資訊網（下稱「銷售資訊網」）（網址：www.srpe.gov.hk），參考「銷售資訊網」內有關一手住宅物業的市場資料 。

- 閱覽賣方就該發展項目所指定的互聯網網站內的有關資訊，包括售樓說明書、價單、載有銷售安排的文件，及成交紀錄冊。

- 發展項目的售樓說明書，會在該項目的出售日期前最少七日向公眾發布，而有關價單和銷售安排，亦會在該項目的出售日期前最少三日公布。

- 在賣方就有關發展項目所指定的互聯網網站，以及「銷售資訊網」內，均載有有關物業成交資料的成交紀錄冊，以供查閱。

2. 費用、按揭貸款和樓價

- 計算置業總開支，包括律師費、按揭費用、保險費，以及印花稅。

- 向銀行查詢可否取得所需的按揭貸款，然後選擇合適的還款方式，並小心計算按揭貸款金額，以確保貸款額沒有超出本身的負擔能力。

- 查閱同類物業最近的成交價格，以作比較。

- 向賣方或地產代理瞭解，您須付予賣方或該發展項目的管理人的預計的管理費、管理費上期金額（如有）、特別基金金額（如有）、補還的水、電力及氣體按金（如有）、以及/或清理廢料的費用（如有）。

3. 價單、支付條款，以及其他財務優惠

- 賣方未必會把價單所涵蓋的住宅物業悉數推售，因此應留意有關的銷售安排，以了解賣方會推售的住宅物業為何。賣方會在有關住宅物業推售日期前最少三日公布銷售安排。

- 留意價單所載列的支付條款。倘買家可就購置有關住宅物業而連帶獲得價格折扣、贈品，或任何財務優惠或利益，上述資訊亦會在價單內列明。

- 如您擬選用由賣方指定的財務機構提供的各類按揭貸款計劃，在簽訂臨時買賣合約前，應先細閱有關價單內列出的按揭貸款計劃資料[1]。如就該些按揭貸款計劃的詳情有任何疑問，應在簽訂臨時買賣合約前，直接向有關財務機構查詢。

4. 物業的面積及四周環境

- 留意載於售樓說明書和價單內的物業面積資料，以及載於價單內的每平方呎/每平方米售價。根據《一手住宅物業銷售條例》（第621章）（下稱「條例」），賣方只可以實用面積表達住宅物業的面積和每平方呎及平方米的售價。就住宅物業而言，實用面積指該住宅物業的樓面面積，包括在構成該物業的一部分的範圍內的以下每一項目的樓面面積：(i) 露台；(ii) 工作平台；以及 (iii) 陽台。實用面積並不包括空調機房、窗台、閣樓、平台、花園、停車位、天台、梯屋、前庭或庭院的每一項目的面積，即使該些項目構成該物業的一部分的範圍。

- 售樓說明書必須顯示發展項目中所有住宅物業的樓面平面圖。在售樓說明書所載有關發展項目中住宅物業的每一份樓面平面圖，均須述明每個住宅物業的外部和內部尺寸[2]。售樓說明書所提供有關住宅物業外部和內部的尺寸，不會把批盪和裝飾物料包括在內。買家收樓前如欲購置家具，應留意這點。

- 親臨發展項目的所在地實地視察，以了解有關物業的四周環境（包括交通和社區設施）；亦應查詢有否任何城市規劃方案和議決，會對有關的物業造成影響；參閱載於售樓說明書內的位置圖、鳥瞰照片、分區計劃大綱圖，以及橫截面圖。

---

1 按揭貸款計劃的資料包括有關按揭貸款計劃對借款人的最低收入的要求、就第一按揭連同第二按揭可獲得的按揭貸款金額上限、最長還款年期、整個還款期內的按揭利率變化，以及申請人須繳付的手續費。

2 根據條例附表1第1部第10(2)(d)條述明，售樓說明書內顯示的發展項目中的住宅物業的每一份樓面平面圖須述明以下各項—
(i) 每個住宅物業的外部尺寸；
(ii) 每個住宅物業的內部尺寸；
(iii) 每個住宅物業的內部間隔的厚度；
(iv) 每個住宅物業內個別分隔室的外部尺寸。
根據條例附表1第1部第10(3)條，如有關發展項目的經批准的建築圖則，提供條例附表1第1部第10(2)(d)條所規定的資料，樓面平面圖須述明如此規定的該資料。

5. 售樓說明書

- 確保所取得的售樓說明書屬最新版本。根據條例，提供予公眾的售樓說明書必須是在之前的三個月之內印製或檢視、或檢視及修改。

- 閱覽售樓說明書，並須特別留意以下資訊：

  - 售樓說明書內有否關於「有關資料」的部分，列出賣方知悉但並非為一般公眾人士所知悉，關於相當可能對享用有關住宅物業造成重大影響的事宜的資料。請注意，已在土地註冊處註冊的文件，其內容不會被視為「有關資料」；

  - 橫截面圖會顯示有關建築物相對毗連該建築物的每條街道的橫截面，以及每條上述街道與已知基準面和該建築物最低的一層住宅樓層的水平相對的水平。橫截面圖能以圖解形式，顯示出建築物最低一層住宅樓層和街道水平的高低差距，不論該最低住宅樓層以何種方式命名；

  - 室內和外部的裝置、裝修物料和設備；

  - 管理費按甚麼基準分擔；

  - 小業主有否責任或需要分擔管理、營運或維持有關發展項目以內或以外的公眾休憩用地或公共設施的開支，以及有關公眾休憩用地或公共設施的位置；以及

  - 小業主是否須要負責維修斜坡。

6. 政府批地文件和公契

- 閱覽政府批地文件和公契（或公契擬稿）。公契內載有天台和外牆業權等相關資料。賣方會在售樓處提供政府批地文件和公契（或公契擬稿）的複本，供準買家免費閱覽。

- 留意政府批地文件內所訂明小業主是否須要負責支付地稅。

- 留意公契內訂明有關物業內可否飼養動物。

7. 售樓處內有關可供揀選住宅物業的資料

- 向賣方查詢清楚有哪些一手住宅物業可供揀選。若賣方在售樓處內展示「消耗表」，您可從該「消耗表」得悉在每個銷售日的銷售進度資料，包括在該個銷售日開始時有哪些住宅物業可供出售，以及在該個銷售日內有哪些住宅物業已獲揀選及售出。

- 切勿隨便相信有關發展項目銷情的傳言，倉卒簽立臨時買賣合約。

8. 成交紀錄冊

- 留意發展項目的成交紀錄冊。賣方須於臨時買賣合約訂立後的 24小時內，於紀錄冊披露該臨時買賣合約的資料，以及於買賣合約訂立後一個工作天內，披露該買賣合約的資料。您可透過成交紀錄冊得悉發展項目的銷售情況。

- 切勿將賣方接獲用作登記的購樓意向書或本票的數目視為銷情指標。發展項目的成交紀錄冊才是讓公眾掌握發展項目每日銷售情況的最可靠資料來源。

9. 買賣合約

- 確保臨時買賣合約和買賣合約包含條例所規定的強制性條文。

- 留意有關物業買賣交易所包括的裝置、裝修物料和設備，須在臨時買賣合約和買賣合約上列明。

- 留意夾附於買賣合約的圖則。該圖則會顯示所有賣方售予您的物業面積，而該面積通常較該物業的實用面積為大。

- 訂立臨時買賣合約時，您須向擁有人（即賣方）支付樓價5%的臨時訂金。

- 如您在訂立臨時買賣合約後**五個工作日**（工作日指並非公眾假日、星期六、黑色暴雨警告日或烈風警告日的日子）之內，沒有簽立買賣合約，該臨時買賣合約即告終止，有關臨時訂金（即樓價的5%）會被沒收，而擁有人（即賣方）不得因您沒有簽立買賣合約而對您提出進一步申索。

- 在訂立臨時買賣合約後的五個工作日之內，倘您簽立買賣合約，則擁有人（即賣方）必須在訂立該臨時買賣合約後的八個工作日之內簽立買賣合約。

- 有關的訂金，應付予負責為所涉物業擔任保證金保存人的律師事務所。

10. 表達購樓意向

- 留意在賣方（包括其獲授權代表）就有關住宅物業向公眾提供價單前，賣方不得尋求或接納任何對有關住宅物業的購樓意向（不論是否屬明確選擇購樓意向）。因此您不應向賣方或其授權代表提出有關意向。

- 留意在有關住宅物業的銷售開始前，賣方（包括其獲授權代表）不得尋求或接納任何對該物業的有明確選擇購樓意向。因此您不應向賣方或其授權代表提出有關意向。

11. 委託地產代理

- 留意倘賣方委任一個或多於一個地產代理，以協助銷售其發展項目內任何指明住宅物業，該發展項目的價單必須列明在價單印刷日期當日所有獲委任為地產代理的姓名/名稱 。

- 您可委託任何地產代理（不一定是賣方所指定的地產代理），以協助您購置發展項目內任何指明住宅物業；您亦可不委託任何地產代理。

- 委託地產代理以物色物業前，您應該 —

  - 了解該地產代理是否只代表您行事。該地產代理若同時代表賣方行事，倘發生利益衝突，未必能夠保障您的最大利益；

  - 了解您須否支付佣金予該地產代理。若須支付，有關的佣金金額和支付日期為何；以及

  - 留意只有持牌地產代理或營業員才可以接受您的委託。如有疑問，應要求該地產代理或營業員出示其「地產代理證」，或瀏覽地產代理監管局的網頁（網址：www.eaa.org.hk），查閱牌照目錄。

12. 委聘律師

- 考慮自行委聘律師，以保障您的利益。該律師若同時代表賣方行事，倘發生利益衝突，未必能夠保障您的最大利益。

- 比較不同律師的收費。

適用於一手未落成住宅物業

13. 預售樓花同意書

- 洽購地政總署「預售樓花同意方案」下的未落成住宅物業時，應向賣方確認地政總署是否已就該發展項目批出「預售樓花同意書」。

14. 示範單位

- 賣方不一定須設置示範單位供準買家或公眾參觀，但賣方如為某指明住宅物業設置示範單位，必須首先設置該住宅物業的無改動示範單位，才可設置該住宅物業的經改動示範單位，並可以就該住宅物業設置多於一個經改動示範單位。

- 參觀示範單位時，務必視察無改動示範單位，以便與經改動示範單位作出比較。然而，條例並沒有限制賣方安排參觀無改動示範單位及經改動示範單位的先後次序。

- 賣方設置示範單位供公眾參觀時，應已提供有關發展項目的售樓說明書。因此，緊記先行索取售樓說明書，以便在參觀示範單位時參閱相關資料。

- 您可以在無改動示範單位及經改動示範單位中進行量度，並在無改動示範單位內拍照或拍攝影片，惟在確保示範單位參觀者人身安全的前提下，賣方可能會設定合理的限制。

適用於一手未落成住宅物業及尚待符合條件的已落成住宅物業

15. 預計關鍵日期及收樓日期

- 查閱售樓說明書中有關發展項目的預計關鍵日期[3]。

  - 售樓說明書中有關發展項目的預計關鍵日期並不等同買家的「收樓日期」。買家的「收樓日期」必定較發展項目的預計關鍵日期遲。

- 收樓日期

  - 條例規定買賣合約須載有強制性條文，列明賣方須於買賣合約內列出的預計關鍵日期後的14日內，以書面為發展項目申請佔用文件、合格證明書，或地政總署署長的轉讓同意（視屬何種情況而定）。

    - ➢ 如發展項目屬地政總署預售樓花同意方案所規管，賣方須在合格證明書或地政總署署長的轉讓同意發出後的一個月內（以較早者為準），就賣方有能力有效地轉讓有關物業一事，以書面通知買家；或

    - ➢ 如發展項目並非屬地政總署預售樓花同意方案所規管，賣方須在佔用文件（包括佔用許可證）發出後的六個月內，就賣方有能力有效地轉讓有關物業一事，以書面通知買家。

  - 條例規定買賣合約須載有強制性條文，列明有關物業的買賣須於賣方發出上述通知的日期的14日內完成。有關物業的買賣完成後，賣方將安排買家收樓事宜。

- 認可人士可批予在預計關鍵日期之後完成發展項目

  - 條例規定買賣合約須載有強制性條文，列明發展項目的認可人士可以在顧及純粹由以下一個或多於一個原因所導致的延遲後，批予在預計關鍵日期之後，完成發展項目：

    - ➢ 工人罷工或封閉工地；

    - ➢ 暴動或內亂；

    - ➢ 不可抗力或天災；

    - ➢ 火警或其他賣方所不能控制的意外；

    - ➢ 戰爭；或

    - ➢ 惡劣天氣。

  - 發展項目的認可人士可以按情況，多於一次批予延後預計關鍵日期以完成發展項目，即收樓日期可能延遲。

  - 條例規定買賣合約須載有強制性條文，列明賣方須於認可人士批予延期後的14日內，向買家提供有關延期證明書的文本。

- 如對收樓日期有任何疑問，可向賣方查詢。

[3] 一般而言，「關鍵日期」指該項目符合批地文件的條件的日期，或該項目在遵照經批准的建築圖則的情況下或按照豁免證明書的發出的條件在各方面均屬完成的日期。有關詳情請參閱條例第2條。

適用於一手已落成住宅物業

16. 賣方資料表格

- 確保取得最近三個月內印製有關您擬購買的一手已落成住宅物業的「賣方資料表格」。

17. 參觀物業

- 購置住宅物業前，確保已獲安排參觀您打算購置的住宅物業。倘參觀有關物業並非合理地切實可行，則應參觀與有關物業相若的物業，除非您以書面同意賣方無須開放與有關物業相若的物業供您參觀。您應仔細考慮，然後才決定是否簽署豁免上述規定的書面同意。

- 除非有關物業根據租約持有，或為確保物業參觀者的人身安全而須設定合理限制，您可以對該物業進行量度、拍照或拍攝影片。

任何與賣方銷售受條例所規管的一手住宅物業有關的投訴和查詢，請與一手住宅物業銷售監管局聯絡。

網址	: www.srpa.gov.hk
電話	: 2817 3313
電郵	: enquiry_srpa@hd.gov.hk
傳真	: 2219 2220

其他相關聯絡資料：

消費者委員會	
網址	: www.consumer.org.hk
電話	: 2929 2222
電郵	: cc@consumer.org.hk
傳真	: 2856 3611
地產代理監管局	
網址	: www.eaa.org.hk
電話	: 2111 2777
電郵	: enquiry@eaa.org.hk
傳真	: 2598 9596
香港地產建設商會	
電話	: 2826 0111
傳真	: 2845 2521

運輸及房屋局
一手住宅物業銷售監管局
2017 年 8 月

Name of the Development
NAPA

Name of the street at which the Development is situated and the street number allocated by the Commissioner of Rating and Valuation for the purpose of distinguishing the Development
88 So Kwun Wat Road

The Development consists of houses and multi-unit buildings
Total number of houses and house numbering
There are 60 houses in total:
House A
House B1-B3 and B5-B9
House C1-C3, C5-C12, C15-C23 and C25-C31
House D1-D3, D5-D12, D15-D23 and D25-D28

Omitted house numbers
House B4, C4,C13,C14,C24,D4,D13,D14 and D24

Total number of storeys of each multi-unit building
There are 5 multi-unit buildings in total:
Tower 1 : 10 storeys
Tower 2 : 10 storeys
Tower 3 : 10 storeys
Tower 5 & 5A : 10 storeys
Tower 6 & 6A : 10 storeys
Note: The above numbers of storeys do not include basements and roofs.

Floor numbering in each multi-unit building
Tower 1 : B1/F, G/F, 1/F-3/F, 5/F-10/F & Roof
Tower 2 : B1/F, G/F, 1/F-3/F, 5/F-10/F & Roof
Tower 3 : B1/F, G/F, 1/F-3/F, 5/F-10/F & Roof
Tower 5 & 5A : B1/F, G/F, 1/F-3/F, 5/F-10/F & Roof
Tower 6 & 6A : B1/F, G/F, 1/F-3/F, 5/F-10/F & Roof

發展項目名稱
NAPA

發展項目所位於的街道名稱及由差餉物業估價署署長為識別發展項目的目的而編配的門牌號數
掃管笏路88號

發展項目包括洋房及多於一幢多單位建築物
洋房的總數及洋房編號
合共60間洋房：
A號洋房
B1-B3及B5-B9號洋房
C1-C3、C5-C12、C15-C23及C25-C31號洋房
D1-D3、D5-D12、D15-D23及D25-D28號洋房

被略去的洋房編號
B4、C4、C13、C14、C24、D4、D13、D14及D24號洋房

每幢多單位建築物的樓層的總數
合共5座多單位建築物：
第1座：10層
第2座：10層
第3座：10層
第5及5A座：10層
第6及6A座：10層
備註：上述樓層數目並不包括地庫及天台

每幢多單位建築物內的樓層號數
第1座：地庫1樓、地下、1樓-3樓、5樓-10樓及天台
第2座：地庫1樓、地下、1樓-3樓、5樓-10樓及天台
第3座：地庫1樓、地下、1樓-3樓、5樓-10樓及天台
第5及5A座：地庫1樓、地下、1樓-3樓、5樓-10樓及天台
第6及6A座：地庫1樓、地下、1樓-3樓、5樓-10樓及天台

Omitted floor numbers in each multi-unit building

4/F for all Towers

Refuge floors of each multi-unit building

No refuge floor for all Towers

每幢多單位建築物內被略去的樓層號數

每座大廈均不設4樓

每幢多單位建築物內的庇護層

每座大廈均不設庇護層

Vendor
Wascott Property Limited

Holding companies of the Vendor
Wheelock and Company Limited
Wheelock Properties Limited
Wheelock Investments Limited
Realty Development Corporation Limited
Myers Investments Limited
Dannette Holdings Limited

Authorized Person for the Development
Chan Kam-tong, Angus

The firm or corporation of which an Authorized Person for the Development is a proprietor, director or employee in his or her professional capacity
P&T Architects and Engineers Limited

Building contractor for the Development
China Overseas Building Construction Limited

The firm of solicitors acting for the owner in relation to the sale of residential properties in the Development
Mayer Brown JSM

Any authorized institution that has made a loan, or has undertaken to provide finance, for the construction of the Development
The Bank of East Asia, Limited
Australia and New Zealand Banking Group Limited
(The mortgage was discharged on 10 January 2018)

Any other person who has made a loan for the construction of the Development
Wheelock Finance Limited

賣方
Wascott Property Limited

賣方的控權公司
會德豐有限公司
會德豐地產有限公司
Wheelock Investments Limited
聯邦地產有限公司
Myers Investments Limited
Dannette Holdings Limited

發展項目的認可人士
陳錦棠

認可人士以其專業身分擔任經營人、董事或僱員的商號或法團
巴馬丹拿建築及工程師有限公司

發展項目的承建商
中國海外房屋工程有限公司

就發展項目中的住宅物業的出售而代表擁有人行事的律師事務所
孖士打律師行

已為發展項目的建造提供貸款或已承諾為該項建造提供融資的認可機構
東亞銀行有限公司
澳新銀行集團有限公司
(有關按揭已於2018年1月10日解除)

已為發展項目的建造提供貸款的任何其他人
Wheelock Finance Limited

(a)	The vendor or a building contractor for the development is an individual, and that vendor or contractor is an immediate family member of an authorized person for the development; 賣方或有關發展項目的承建商屬個人，並屬該項目的認可人士的家人；	Not applicable 不適用
(b)	The vendor or a building contractor for the development is a partnership, and a partner of that vendor or contractor is an immediate family member of such an authorized person; 賣方或該項目的承建商屬合夥，而該賣方或承建商的合夥人屬上述認可人士的家人；	Not applicable 不適用
(c)	The vendor or a building contractor for the development is a corporation, and a director or the secretary of that vendor or contractor (or a holding company of that vendor) is an immediate family member of such an authorized person; 賣方或該項目的承建商屬法團，而該賣方或承建商(或該賣方的控權公司)的董事或秘書屬上述認可人士的家人；	No 否
(d)	The vendor or a building contractor for the development is an individual, and that vendor or contractor is an immediate family member of an associate of such an authorized person; 賣方或該項目的承建商屬個人，並屬上述認可人士的有聯繫人士的家人；	Not applicable 不適用
(e)	The vendor or a building contractor for the development is a partnership, and a partner of that vendor or contractor is an immediate family member of an associate of such an authorized person; 賣方或該項目的承建商屬合夥，而該賣方或承建商的合夥人屬上述認可人士的有聯繫人士的家人；	Not applicable 不適用
(f)	The vendor or a building contractor for the development is a corporation, and a director or the secretary of that vendor or contractor (or a holding company of that vendor) is an immediate family member of an associate of such an authorized person; 賣方或該項目的承建商屬法團，而該賣方或承建商(或該賣方的控權公司)的董事或秘書屬上述認可人士的有聯繫人士的家人；	No 否
(g)	The vendor or a building contractor for the development is an individual, and that vendor or contractor is an immediate family member of a proprietor of a firm of solicitors acting for the owner in relation to the sale of residential properties in the development; 賣方或該項目的承建商屬個人，並屬就該項目內的住宅物業的出售代表擁有人行事的律師事務所行事的經營人的家人；	Not applicable 不適用
(h)	The vendor or a building contractor for the development is a partnership, and a partner of that vendor or contractor is an immediate family member of a proprietor of a firm of solicitors acting for the owner in relation to the sale of residential properties in the development; 賣方或該項目的承建商屬合夥，而該賣方或承建商的合夥人屬就該項目內的住宅物業的出售代表擁有人行事的律師事務所行事的經營人的家人；	Not applicable 不適用
(i)	The vendor or a building contractor for the development is a corporation, and a director or the secretary of that vendor or contractor (or a holding company of that vendor) is an immediate family member of a proprietor of such a firm of solicitors; 賣方或該項目的承建商屬法團，而該賣方或承建商(或該賣方的控權公司)的董事或秘書屬上述律師事務所的經營人的家人；	No 否
(j)	The vendor, a holding company of the vendor, or a building contractor for the development, is a private company, and an authorized person for the development, or an associate of such an authorized person, holds at least 10% of the issued shares in that vendor, holding company or contractor; 賣方、賣方的控權公司或有關發展項目的承建商屬私人公司，而該項目的認可人士或該認可人士的有聯繫人士持有該賣方、控權公司或承建商最少10%的已發行股份；	No 否
(k)	The vendor, a holding company of the vendor, or a building contractor for the development, is a listed company, and such an authorized person, or such an associate, holds at least 1% of the issued shares in that vendor, holding company or contractor; 賣方、賣方的控權公司或該項目的承建商屬上市公司，而上述認可人士或上述有聯繫人士持有該賣方、控權公司或承建商最少1%的已發行股份；	No 否
(l)	The vendor or a building contractor for the development is a corporation, and such an authorized person, or such an associate, is an employee, director or secretary of that vendor or contractor or of a holding company of that vendor; 賣方或該項目的承建商屬法團，而上述認可人士或上述有聯繫人士屬該賣方、承建商或該賣方的控權公司的僱員、董事或秘書；	No 否
(m)	The vendor or a building contractor for the development is a partnership, and such an authorized person, or such an associate, is an employee of that vendor or contractor; 賣方或該項目的承建商屬合夥，而上述認可人士或上述有聯繫人士屬該賣方或承建商的僱員；	Not applicable 不適用
(n)	The vendor, a holding company of the vendor, or a building contractor for the development, is a private company, and a proprietor of a firm of solicitors acting for the owner in relation to the sale of residential properties in the development holds at least 10% of the issued shares in that vendor, holding company or contractor; 賣方、賣方的控權公司或該項目的承建商屬私人公司，而就該項目中的住宅物業的出售而代表擁有人行事的律師事務所的經營人持有該賣方、控權公司或承建商最少10%的已發行股份；	No 否
(o)	The vendor, a holding company of the vendor, or a building contractor for the development, is a listed company, and a proprietor of such a firm of solicitors holds at least 1% of the issued shares in that vendor, holding company or contractor; 賣方、賣方的控權公司或該項目的承建商屬上市公司，而上述律師事務所的經營人持有該賣方、控權公司或承建商最少1%的已發行股份；	No 否
(p)	The vendor or a building contractor for the development is a corporation, and a proprietor of such a firm of solicitors is an employee, director or secretary of that vendor or contractor or of a holding company of that vendor; 賣方或該項目的承建商屬法團，而上述律師事務所的經營人屬該賣方或承建商或該賣方的控權公司的僱員、董事或秘書；	No 否
(q)	The vendor or a building contractor for the development is a partnership, and a proprietor of such a firm of solicitors is an employee of that vendor or contractor; 賣方或該項目的承建商屬合夥，而上述律師事務所的經營人屬該賣方或承建商的僱員；	Not applicable 不適用
(r)	The vendor or a building contractor for the development is a corporation, and the corporation of which an authorized person for the development is a director or employee in his or her professional capacity is an associate corporation of that vendor or contractor or of a holding company of that vendor; 賣方或該項目的承建商屬法團，而該項目的認可人士以其專業身分擔任董事或僱員的法團為該賣方或承建商或該賣方的控權公司的有聯繫法團；	No 否
(s)	The vendor or a building contractor for the development is a corporation, and that contractor is an associate corporation of that vendor or of a holding company of that vendor. 賣方或該項目的承建商屬法團，而該承建商屬該賣方或該賣方的控權公司的有聯繫法團。	No 否

There are non-structural prefabricated external walls forming part of the enclosing walls of the Development.
發展項目有構成圍封牆的一部份的非結構的預製外牆。

The thickness of the non-structural prefabricated external walls of each house is 150mm.
每幢洋房的非結構的預製外牆之厚度為150毫米。

Total Area Schedule of the Non-structural Prefabricated External Walls of Each Residential Property
每個住宅物業的非結構的預製外牆的總面積表

House Number* 洋房編號*	Total area of the non-structural prefabricated external walls of each residential property (sq.m) 每個住宅物業的非結構的預製外牆的總面積 (平方米)
House A A號洋房	5.650
House B1 - B9 B1至B9號洋房	5.756
House C1 - C19, C22 - C31 C1至C19，C22至C31號洋房	5.314
House C20 - C21 C20至C21號洋房	3.452
House D1 - D28 D1至D28號洋房	4.328

* House B4, C4, C13, C14, C24, D4, D13,D14 & D24 are omitted.
* 不設B4、C4、C13、C14、C24、D4、D13、D14 及 D24號洋房。

The thickness of the non-structural prefabricated external walls of Tower 1, Tower 2, Tower 3, Towers 5 & 5A and Towers 6 & 6A is 150mm.
第1座、第2座、第3座、第5及5A座、第6及6A座的非結構的預製外牆之厚度為150毫米。

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the non-structural prefabricated external walls of each residential property (sq.m) 每個住宅物業的非結構的預製外牆的總面積 (平方米)
Tower 1 第1座	G/F 地下	A	-
		B	-
		C	-
		D	0.248
		F	0.353
	1/F 1樓	A	-
		B	-
		C	-
		D	0.248
		F	0.353
	2/F - 3/F, 5/F - 10/F 2樓至3樓，5樓至10樓	A	-
		B	-
		C	-
		D	0.240
		E	0.233
		F	0.353

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the non-structural prefabricated external walls of each residential property (sq.m) 每個住宅物業的非結構的預製外牆的總面積 (平方米)
Tower 2 第2座	G/F 地下	B	-
		C	-
		D	-
		E	-
		F	0.403
	1/F 1樓	B	-
		C	-
		D	-
		E	-
		F	0.403
	2/F - 3/F, 5/F - 10/F 2樓至3樓，5樓至10樓	A	0.225
		B	-
		C	-
		D	-
		E	-
		F	0.403

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the non-structural prefabricated external walls of each residential property (sq.m) 每個住宅物業的非結構的預製外牆的總面積 (平方米)
Tower 3 第3座	G/F 地下	B	0.240
		C	-
		D	0.240
		E	0.240
		F	0.278
		G	0.323
	1/F 1樓	B	0.240
		C	-
		D	0.240
		E	0.240
		F	0.278
		G	0.323
	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	0.233
		B	0.233
		C	-
		D	0.240
		E	0.240
		F	0.278
		G	0.323
	10/F 10樓	A	0.360
		B	0.233
		C	-
		D	0.240
		E	0.240
		F	0.240

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the non-structural prefabricated external walls of each residential property (sq.m) 每個住宅物業的非結構的預製外牆的總面積 (平方米)
Tower 5 第5座	G/F 地下	B	0.233
		C	-
		D	-
		E	0.225
	1/F 1樓	A	-
		B	0.233
		C	-
		D	-
		E	0.225
	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	-
		B	0.233
		C	-
		D	-
		E	0.225
		F	-
	10/F 10樓	A	-
		B	0.233
		C	-
		D	-
		E	0.225
		F	-

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the non-structural prefabricated external walls of each residential property (sq.m) 每個住宅物業的非結構的預製外牆的總面積 (平方米)
Tower 5A 第5A座	G/F 地下	C	0.233
		D	0.233
		E	0.233
	1/F 1樓	A	0.240
		C	0.233
		D	0.233
		E	0.233
	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	0.233
		B	0.233
		C	0.233
		D	0.233
		E	0.233
	10/F 10樓	A	0.465
		C	0.233
		D	0.233
		E	0.233

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the non-structural prefabricated external walls of each residential property (sq.m) 每個住宅物業的非結構的預製外牆的總面積 (平方米)
Tower 6 第6座	G/F 地下	A	0.233
		B	0.233
		D	0.244
		E	0.225
		F	0.225
		G	0.270
	1/F 1樓	A	0.233
		B	0.233
		D	0.244
		E	0.225
		F	0.225
		G	0.270
	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	0.233
		B	0.233
		C	0.236
		D	0.236
		E	0.225
		F	0.225
		G	0.270
	10/F 10樓	A	0.465
		C	0.236
		D	0.236
		E	0.225
		F	0.225
		G	0.270

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the non-structural prefabricated external walls of each residential property (sq.m) 每個住宅物業的非結構的預製外牆的總面積 (平方米)
Tower 6A 第6A座	G/F 地下	C	-
		D	-
		E	-
	1/F 1樓	B	-
		C	-
		D	-
		E	-
	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	0.233
		B	0.233
		C	-
		D	-
		E	-
	10/F 10樓	A	0.233
		B	0.233
		C	-
		D	-
		E	-

There are curtain walls forming part of the enclosing walls of the Development.
發展項目有構成圍封牆的一部份的幕牆。

The thickness of the curtain walls of each house is 195-300mm.
每幢洋房的幕牆之厚度為195至300毫米。

Total Area Schedule of the Curtain Walls of Each Residential Property
每個住宅物業的幕牆的總面積表

House Number* 洋房編號*	Total area of the curtain walls of each residential property (sq.m) 每個住宅物業的幕牆的總面積 (平方米)
House A A號洋房	6.837
House B1 - B9 B1至B9號洋房	5.903
House C1-C19, C22-C31 C1至C19，C22至C31號洋房	3.713
House C20-C21 C20至C21號洋房	6.258
House D1 - D28 D1至D28號洋房	3.058

* House B4, C4, C13, C14, C24, D4, D13,D14 & D24 are omitted.
* 不設B4、C4、C13、C14、C24、D4、D13、D14 及 D24號洋房。

The thickness of the curtain walls of Tower 1, Tower 2, Tower 3, Towers 5 & 5A and Towers 6 & 6A of the Development is 195-300mm.
發展項目的第1座，第2座，第3座，第5及5A座，第6及6A座的幕牆之厚度為195至300毫米。

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the curtain walls of each residential property (sq.m) 每個住宅物業的幕牆的總面積 (平方米)
Tower 1 第1座	G/F 地下	A	2.572
		B	2.017
		C	2.017
		D	1.634
		F	1.364
	1/F 1樓	A	2.572
		B	2.017
		C	2.017
		D	1.634
		F	1.364
	2/F 2樓	A	2.572
		B	2.017
		C	2.017
		D	1.634
		E	0.886
		F	1.364
	3/F, 5/F - 10/F 3樓，5樓至10樓	A	2.572
		B	2.017
		C	2.017
		D	1.634
		E	1.364
		F	1.364

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the curtain walls of each residential property (sq.m) 每個住宅物業的幕牆的總面積 (平方米)
Tower 2 第2座	G/F 地下	B	1.222
		C	1.364
		D	1.364
		E	1.222
		F	1.364
	1/F 1樓	B	1.222
		C	1.364
		D	1.364
		E	1.222
		F	1.364
	2/F 2樓	A	0.886
		B	1.222
		C	1.364
		D	1.364
		E	1.222
		F	1.364
	3/F, 5/F-10/F 3樓，5樓至10樓	A	1.364
		B	1.222
		C	1.364
		D	1.364
		E	1.222
		F	1.364

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the curtain walls of each residential property (sq.m) 每個住宅物業的幕牆的總面積 (平方米)
Tower 3 第3座	G/F 地下	B	1.461
		C	1.416
		D	1.296
		E	1.296
		F	1.431
		G	1.341
	1/F 1樓	B	1.461
		C	1.416
		D	1.296
		E	1.296
		F	1.431
		G	2.054
	2/F 2樓	A	1.551
		B	1.461
		C	1.416
		D	1.296
		E	1.296
		F	1.431
		G	1.341
	3/F, 5/F-9/F 3樓，5樓至9樓	A	2.002
		B	1.461
		C	1.416
		D	1.296
		E	1.296
		F	1.431
		G	1.341
	10/F 10樓	A	3.784
		B	1.461
		C	1.416
		D	1.296
		E	1.296
		F	1.431

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the curtain walls of each residential property (sq.m) 每個住宅物業的幕牆的總面積 (平方米)
Tower 5 第5座	G/F 地下	B	1.349
		C	1.326
		D	1.664
		E	1.401
	1/F 1樓	A	1.468
		B	1.349
		C	1.326
		D	1.664
		E	1.401
	2/F 2樓	A	2.077
		B	1.349
		C	1.326
		D	1.664
		E	1.401
		F	0.861
	3/F, 5/F - 9/F 3樓，5樓至9樓	A	2.077
		B	1.349
		C	1.326
		D	1.664
		E	1.401
		F	1.326
	10/F 10樓	A	2.077
		B	1.349
		C	1.326
		D	1.664
		E	1.401
		F	1.326

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the curtain walls of each residential property (sq.m) 每個住宅物業的幕牆的總面積 (平方米)
Tower 5A 第5A座	G/F 地下	C	1.326
		D	1.326
		E	1.364
	1/F 1樓	A	1.408
		C	1.326
		D	1.326
		E	1.364
	2/F 2樓	A	2.017
		B	1.566
		C	1.326
		D	1.326
		E	1.364
	3/F, 5/F - 9/F 3樓，5樓至9樓	A	2.017
		B	2.017
		C	1.326
		D	1.326
		E	1.364
	10/F 10樓	A	5.004
		C	1.326
		D	1.326
		E	1.364

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the curtain walls of each residential property (sq.m) 每個住宅物業的幕牆的總面積 (平方米)
Tower 6 第6座	G/F 地下	A	2.032
		B	2.032
		D	1.957
		E	1.341
		F	1.364
		G	1.454
	1/F 1樓	A	2.032
		B	2.032
		D	1.957
		E	1.341
		F	1.364
		G	1.454
	2/F 2樓	A	2.032
		B	2.032
		C	1.515
		D	1.957
		E	1.341
		F	1.364
		G	1.238
	3/F, 5/F - 9/F 3樓，5樓至9樓	A	2.031
		B	2.031
		C	1.972
		D	1.957
		E	1.341
		F	1.364
		G	1.454
	10/F 10樓	A	4.107
		C	1.972
		D	1.957
		E	1.341
		F	1.364
		G	1.238

Tower Name 大廈名稱	Floor 樓層	Unit 單位	Total area of the curtain walls of each residential property (sq.m) 每個住宅物業的幕牆的總面積 (平方米)
Tower 6A 第6A座	G/F 地下	C	1.311
		D	1.364
		E	1.349
	1/F 1樓	B	0.947
		C	1.311
		D	1.364
		E	1.349
	2/F 2樓	A	1.363
		B	1.341
		C	1.311
		D	1.364
		E	1.349
	3/F, 5/F - 9/F 3樓，5樓至9樓	A	1.957
		B	1.341
		C	1.311
		D	1.364
		E	1.349
	10/F 10樓	A	1.957
		B	1.341
		C	1.311
		D	1.364
		E	1.349

Harriman Property Management Limited will be appointed as the manager of the Development under the deed of mutual covenant incorporating a management agreement that has been executed or the latest draft deed of mutual covenant incorporating a management agreement as at the date on which the sales brochure is printed (as the case may be) .

根據已簽立的公契及管理協議或有關公契及管理協議在該售樓說明書的印製日期的最新擬稿（視乎情況），夏利文物業管理有限公司將獲委任為發展項目的管理人。

7 LOCATION PLAN OF THE DEVELOPMENT
發展項目的所在位置圖



Location of the Development
發展項目的位置

Scale :
比例
0M/米 250M/米

N

Street name(s) not shown in full in the Location Plan of the Development:
於發展項目的所在位置圖未能顯示之街道全名：

*Ka Wo Li Hill Road 嘉和里山路

#Ka Choi Lane 嘉財里

The above Location Plan is prepared based on a reproduction of Survey Sheet No. 6-SW-C dated 29 March 2018 with adjustments where necessary.
上述所在位置圖使用日期為2018年3月29日之測繪圖（編號6-SW-C），複印後修正處理。

Legend 圖例

- Public Carpark (including Lorry Park)
  公眾停車場（包括貨車停泊處）
- Power plant (including Electricity Sub-stations)
  發電廠（包括電力分站）
- Public Transport Terminal (including Rail Station)
  公共交通總站（包括鐵路車站）
- Public Utility Installation
  公用事業設施裝置
- Refuse Collection Point
  垃圾收集站
- Religious Institution (including Church, Temple and Tsz Tong)
  宗教場所（包括教堂、廟宇及祠堂）
- School (including Kindergarten)
  學校（包括幼稚園）

Notes:

1. Due to technical reasons as a result of the irregular boundary of the Development, the Location Plan has shown more than the area required under the "Residential Properties (First-hand Sales) Ordinance".
2. The map reproduced with permission of the Director of Lands © The Government of Hong Kong SAR. Licence No. 36/2016.
3. The vendor advises prospective purchasers to conduct an on-site visit for a better understanding of the development site, its surrounding environment and the public facilities nearby.

附註：

1. 因發展項目的不規則界線引致的技術原因，所在位置圖所顯示的範圍多於《一手住宅物業銷售條例》所要求。
2. 地圖版權屬香港特別行政區政府，經地政總署准許複印，版權特許編號36/2016。
3. 賣方建議準買方到該發展地盤作實地考察，以對該發展地盤、其周邊地區環境及附近的公共設施有較佳了解。

AERIAL PHOTOGRAPH OF THE DEVELOPMENT
發展項目的鳥瞰照片



Location of the Development
發展項目的位置

N

Adopted from part of the aerial photograph taken by the Survey and Mapping Office of Lands Department at a flying height of 6,900 feet, photo No. E017158C, date of flight: 2nd April 2017.

Survey and Mapping Office, Lands Department, The Government of HKSAR © Copyright reserved - reproduction by permission only.

摘錄自地政總署測繪處在6,900呎的飛行高度拍攝之鳥瞰照片，照片編號E017158C，飛行日期：2017年4月2日。

香港特別行政區政府地政總署測繪處©版權所有，未經許可，不得複製。

Notes :

1. Copy of the aerial photograph of the Development is available for free inspection at the sales office during opening hours.
2. The aerial photograph may show more than the area required under the Residential Properties (First-hand Sales) Ordinance due to technical reason that the boundary of the Development is irregular.

附註：

1. 發展項目的鳥瞰照片之副本可於售樓處開放時間內免費查閱。
2. 由於發展項目的邊界不規則的技術原因，鳥瞰照片所顯示的範圍可能多於《一手住宅物業銷售條例》所要求顯示的範圍。



Location of the Development
發展項目的位置

N

Adopted from part of the aerial photograph taken by the Survey and Mapping Office of Lands Department at a flying height of 6,900 feet, photo No. E027326C, date of flight: 29th May 2017.

Survey and Mapping Office, Lands Department, The Government of HKSAR © Copyright reserved - reproduction by permission only.

摘錄自地政總署測繪處在6,900呎的飛行高度拍攝之鳥瞰照片，照片編號E027326C，飛行日期：2017年5月29日。

香港特別行政區政府地政總署測繪處©版權所有，未經許可，不得複製。

Notes :

1. Copy of the aerial photograph of the Development is available for free inspection at the sales office during opening hours.
2. The aerial photograph may show more than the area required under the Residential Properties (First-hand Sales) Ordinance due to technical reason that the boundary of the Development is irregular.

附註：

1. 發展項目的鳥瞰照片之副本可於售樓處開放時間內免費查閱。
2. 由於發展項目的邊界不規則的技術原因，鳥瞰照片所顯示的範圍可能多於《一手住宅物業銷售條例》所要求顯示的範圍。

OUTLINE ZONING PLAN RELATING TO THE DEVELOPMENT
關乎發展項目的分區計劃大綱圖

Part of the Draft Tuen Mun Outline Zoning Plan No. S/TM/34 gazetted on 3 November 2017.
Survey and Mapping Office, Lands Department, The Government of HKSAR © Copyright reserved - reproduction by permission only.
摘錄自2017年11月3日憲報公布之屯門分區計劃大綱草圖，圖則編號 S/TM/34。
香港特別行政區政府地政總署測繪處©版權所有，未經許可，不得複製。

Location of the Development
發展項目的位置

Scale :
比例
0M/米 500M/米

Notation 圖例

Zones 地帶

Comprehensive Development Area 綜合發展區	CDA
Residential (Group B) 住宅(乙類)	R(B)
Village Type Development 鄉村式發展	V
Government, Institution or Community 政府、機構或社區	G/IC
Open Space 休憩用地	O
Green Belt 綠化地帶	GB

Communications 交通

Major Road and Junction 主要道路及路口

Miscellaneous 其他

Boundary of Planning Scheme 規劃範圍界線

Planning Area Number 規劃區編號 (1)

Maximum Building Height
(In Metres Above Principal Datum)
最高建築物高度（在主水平基準上若干米） 100

Maximum Building Height
Restriction as Stipulated on The Notes
《註釋》內訂明最高建築物高度限制

Maximum Building Height (In Number of Storeys)
最高建築物高度（樓層數目） 3

Non-Building Area 非建築用地 NBA

核准圖編號 S/TM/33 的修訂
AMENDMENTS TO APPROVED PLAN No. S/TM/33

AMENDMENTS EXHIBITED UNDER SECTION 5 OF THE TOWN PLANNING ORDINANCE
按照城市規劃條例第5條展示的修訂

AMENDMENT ITEMS D1,D2
修訂項目D1,D2項

Notes:

1. The Outline Zoning Plan is an excerpt of the Draft Tuen Mun Outline Zoning Plan No. S/TM/34 gazetted on 3 November 2017, with adjustments where necessary as shown in red.
2. Due to technical reasons (such as the shape of the Development), the Outline Zoning Plan has shown more than the area required under the Residential Properties (First-hand Sales) Ordinance.

附註：

1. 分區計劃大綱圖摘錄自2017年11月3日憲報公布之屯門分區計劃大綱草圖編號S/TM/34，有需要的地方經修正處理，以紅色顯示。
2. 由於技術原因（例如發展項目之形狀），分區計劃大綱圖所顯示的範圍多於《一手住宅物業銷售條例》所要求顯示的範圍。

OUTLINE ZONING PLAN RELATING TO THE DEVELOPMENT
關乎發展項目的分區計劃大綱圖



Part of the Approved So Kwun Wat Outline Zoning Plan No. S/TM-SKW/13 gazetted on 11 December 2015.

Survey and Mapping Office, Lands Department, The Government of HKSAR © Copyright reserved - reproduction by permission only.

摘錄自2015年12月11日憲報公布之掃管笏分區計劃大綱核准圖，圖則編號 S/TM-SKW/13。

香港特別行政區政府地政總署測繪處©版權所有，未經許可，不得複製。

Location of the Development
發展項目的位置

Scale :
比例
0M/米 500M/米

Notation 圖例

Zones 地帶

Residential (Group B) 住宅(乙類)	R(B)
Residential (Group C) 住宅(丙類)	R(C)
Village Type Development 鄉村式發展	V
Government, Institution or Community 政府、機構或社區	G/IC
Green Belt 綠化地帶	GB

Communications 交通

Major Road and Junction 主要道路及路口

Miscellaneous 其他

Boundary of Planning Scheme 規劃範圍界線

Maximum Building Height
(In Metres Above Principal Datum)
最高建築物高度（在主水平基準上若干米） 100

Maximum Building Height
Restriction as Stipulated on The Notes
《註釋》內訂明最高建築物高度限制

Maximum Building Height (In Number of Storeys)
最高建築物高度（樓層數目） 3

Notes:

1. The Outline Zoning Plan is an excerpt of the Approved So Kwun Wat Outline Zoning Plan No. S/TM-SKW/13 gazetted on 11 December 2015, with adjustments where necessary as shown in red.
2. Due to technical reasons (such as the shape of the Development), the Outline Zoning Plan has shown more than the area required under the Residential Properties (First-hand Sales) Ordinance.

附註：

1. 分區計劃大綱圖摘錄自2015年12月11日憲報公布之掃管笏分區計劃大綱核准圖編號 S/TM-SKW/13，有需要的地方經修正處理，以紅色顯示。
2. 由於技術原因（例如發展項目之形狀），分區計劃大綱圖所顯示的範圍多於《一手住宅物業銷售條例》所要求顯示的範圍。

Boundary of the Development
發展項目的界線

Scale : 0M/米 20M/米
比例

11 FLOOR PLANS OF RESIDENTIAL PROPERTIES IN THE DEVELOPMENT
發展項目的住宅物業的樓面平面圖

Notes :

- There are architectural features, metal grilles and/or exposed pipes on the external walls of some of the floors. For details, please refer to the latest approved building plans.
- Common pipes exposed and/or enclosed in cladding are located at/adjacent to the balcony and/or flat roof and/or air-conditioner platform and/or external wall of some residential units. For details, please refer to the latest approved building plans and/or approved drainage plans.
- There are sunken slabs (for mechanical & electrical services of units above) and/or ceiling bulkheads for the air-conditioning fittings and/or mechanical & electrical services at some residential units.
- There are exposed pipes installed in some stores and toilets.
- There are exposed pipes located at the upper part of some utility platforms.
- Balconies and utility platforms are non-enclosed areas.
- Symbols of fittings and fitments such as bath tub, sink, water closet, shower, sink counter, etc. are prepared based on the latest approved building plans and are for general indication only.

備註：

- 部分樓層外牆範圍設有建築裝飾、金屬格柵及/或外露喉管，詳細資料請參考最新批准的建築圖則。
- 部分住宅單位的露台及/或平台及/或空調機平台及/或外牆上/附近設有外露及/或外牆裝飾板內藏之公用喉管，詳細資料請參考最新批准的建築圖則及/或排水設施圖。
- 部分住宅單位天花有跌級樓板(用以安裝樓上單位之機電設備)及/或假天花內裝置空調裝備及/或其他機電設備。
- 部分儲物房及洗手間內裝有外露喉管。
- 部分工作平台上方裝有外露喉管。
- 露台及工作平台為不可封閉的地方。
- 樓面平面圖上所顯示的裝置符號，如浴缸、洗滌盆、座廁、花灑、洗滌盆櫃等乃按最新的經批准的建築圖則繪製，只作一般示意用途。

Legend 圖例

A/C PLATFORM = AIR CONDITIONER PLATFORM = 空調機平台	H.R. = HOSE REEL = 消防喉轆
A/C = AIR CONDITIONER = 空調機	KIT. = KITCHEN = 廚房
A.F. = ARCHITECTURAL FEATURE = 建築裝飾	LIV. = LIVING ROOM = 客廳
ALUMINIUM A.F. = ALUMINIUM ARCHITECTURAL FEATURE = 鋁質建築裝飾	L.W. = LIGHT WELL = 採光天井
A.D. = AIR DUCT = 排氣管	LAV. = LAVATORY = 洗手間
BAL = BALCONY = 露台	M.BATH = MASTER BATHROOM = 主人浴室
BATH = BATHROOM = 浴室	MBR = MASTER BEDROOM = 主人睡房
BR1 = BEDROOM 1 = 睡房1	P.D. = PIPE DUCT = 管道槽
BR2 = BEDROOM 2 = 睡房2	P.W. = PIPE WELL = 管井
BR3 = BEDROOM 3 = 睡房3	R.S. & M.R.R. = REFUSE STORAGE AND MATERIAL RECOVERY ROOM = 垃圾及物料回收室
CONC. = CONCRETE = 混凝土	STONE A.F. = STONE ARCHITECTURAL FEATURE = 石材建築裝飾
DIN. = DINING ROOM = 飯廳	STORE = STORE ROOM = 儲物房
DN = DOWN = 落	TCR = TELECOMMUNICATION CABLE RISER ROOM = 電訊機房
ELV = EXTRA LOW VOLTAGE ELECTRICAL DUCT ROOM = 特低壓電管道房	TBE = TELECOMMUNICATION BROADCASTING EQUIPMENT ROOM = 電訊及廣播設備室
EMC = ELECTRICAL METER CABINET = 電錶櫃	UP. = UTILITY PLATFORM = 工作平台
EL = ELECTRICAL ROOM = 電機房	UP = 上
F.S. CONTROL ROOM = FIRE SERVICES CONTROL ROOM = 消防控制室	WMC = WATER METER CABINET = 水錶櫃
F.S. INLET = FIRE SERVICES INLET = 消防喉入水掣	

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House A A號洋房	200	150, 175, 250	150, 175, 250	150, 200, 250	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3950, 3975, 4200	3175, 3225, 3500, 3725, 3750	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House A Floor Plan
A號洋房 樓面平面圖

B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖



1/F Floor Plan
1樓平面圖

2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House B1 B1號洋房	200	150, 175, 200, 225	150, 200	150, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3975, 4200	3175, 3225, 3450, 3500, 3725, 3775	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House B1 Floor Plan
B1號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖



1/F Floor Plan
1樓平面圖



2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House B2 B2號洋房	200	150, 175, 200, 225	150, 200	150, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3975, 4200	3175, 3225, 3450, 3500, 3725, 3775	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House B2 Floor Plan
B2號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖



1/F Floor Plan
1樓平面圖



2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House B3 B3號洋房	200	150, 175, 200, 225	150, 200	150, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3975, 4200	3175, 3225, 3450, 3500, 3725, 3775	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House B3 Floor Plan
B3號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖

1/F Floor Plan
1樓平面圖

2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House B5 B5號洋房	200	150, 175, 200, 225	150, 200	150, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3975, 4200	3175, 3225, 3450, 3500, 3725, 3775	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House B5 Floor Plan
B5號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖



1/F Floor Plan
1樓平面圖



2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House B6 B6號洋房	200	150, 175, 200, 225	150, 200	150, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3975, 4200	3175, 3225, 3450, 3500, 3725, 3775	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House B6 Floor Plan
B6號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖



1/F Floor Plan
1樓平面圖



2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House B7 B7號洋房	200	150, 175, 200, 225	125, 150, 200	125, 150, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3975, 4200	3175, 3225, 3450, 3500, 3725, 3775	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House B7 Floor Plan
B7號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖



1/F Floor Plan
1樓平面圖



2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House B8 B8號洋房	200	150, 175, 200, 225	150, 200	150, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3975, 4200	3175, 3225, 3450, 3500, 3725, 3775	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House B8 Floor Plan
B8號洋房 樓面平面圖

N



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖



1/F Floor Plan
1樓平面圖



2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House B9 B9號洋房	200	150, 175, 200, 225	150, 200	150, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3975, 4200	3175, 3225, 3450, 3500, 3725, 3775	3500, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House B9 Floor Plan
B9號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



Roof Plan
天台平面圖



Upper Roof Plan
上層天台平面圖



1/F Floor Plan
1樓平面圖



2/F Floor Plan
2樓平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C1 C1號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200, 4700	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C1 Floor Plan
C1號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C2 C2號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C2 Floor Plan
C2號洋房 樓面平面圖

N

Upper Roof Plan
上層天台平面圖







B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C3 C3號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C3 Floor Plan
C3號洋房 樓面平面圖

N

Upper Roof Plan
上層天台平面圖





B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C5 C5號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C5 Floor Plan
C5號洋房 樓面平面圖

N

Upper Roof Plan
上層天台平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	2/F 2樓	Roof 天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C6 C6號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C6 Floor Plan
C6號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C7 C7號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200, 4800	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C7 Floor Plan
C7號洋房 樓面平面圖

N

Upper Roof Plan
上層天台平面圖



B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C8 C8號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200, 4700	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C8 Floor Plan
C8號洋房 樓面平面圖

N

Upper Roof Plan
上層天台平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C9 C9號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 4475, 4700	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C9 Floor Plan
C9號洋房 樓面平面圖

N



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C10 C10號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C10 Floor Plan
C10號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C11 C11號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C11 Floor Plan
C11號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C12 C12號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C12 Floor Plan
C12號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C15 C15號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C15 Floor Plan
C15號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C16 C16號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200, 5550	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C16 Floor Plan
C16號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C17 C17號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200, 5550	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C17 Floor Plan
C17號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C18 C18號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200, 5550	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C18 Floor Plan
C18號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C19 C19號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C19 Floor Plan
C19號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C20 C20號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C20 Floor Plan
C20號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C21 C21號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 4700	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C21 Floor Plan
C21號洋房 樓面平面圖

N

Upper Roof Plan
上層天台平面圖





停車場
CARPARK

B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C22 C22號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C22 Floor Plan
C22號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C23 C23號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C23 Floor Plan
C23號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C25 C25號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C25 Floor Plan
C25號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C26 C26號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C26 Floor Plan
C26號洋房 樓面平面圖

*This part of House C26 has been altered by way of minor works or exempted building works under the Building Ordinance after completion of the development, the latest condition of which is shown on the relevant part plan. The alteration is as follows:-

1. Glass sliding door is added between Master Bedroom and Walk-In Closet.

*洋房C 26此部分因在發展項目落成後進行小型工程或獲“建築物條例”豁免的工程而有所改動，現狀請參閱有關部分平面圖。該等改動如下：-

1.一樓主人睡房及衣帽間中間增加玻璃趟門。

Part Plan Showing Latest Layout
現狀間隔部份平面圖

Upper Roof Plan
上層天台平面圖









B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C27 C27號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C27 Floor Plan
C27號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C28 C28號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C28 Floor Plan
C28號洋房 樓面平面圖



停車場
CARPARK

B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Upper Roof Plan
上層天台平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C29 C29號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C29 Floor Plan
C29號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C30 C30號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C30 Floor Plan
C30號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House C31 C31號洋房	200	150, 175, 200, 225	150, 175, 200	200	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 3975, 4200	3500, 3725, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House C31 Floor Plan
C31號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D1 D1號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 4425, 4700, 5425, 5700	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D1 Floor Plan
D1號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D2 D2號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 4425, 4700, 5425, 5700	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D2 Floor Plan
D2號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Upper Roof Plan
上層天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D3 D3號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 4425, 4700, 5425, 5700	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D3 Floor Plan
D3號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D5 D5號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 4425, 4700, 5425, 5700	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D5 Floor Plan
D5號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D6 D6號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D6 Floor Plan
D6號洋房 樓面平面圖





Upper Roof Plan
上層天台平面圖



B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D7 D7號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D7 Floor Plan
D7號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D8 D8號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D8 Floor Plan
D8號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D9 D9號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D9 Floor Plan
D9號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D10 D10號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D10 Floor Plan
D10號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D11 D11號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D11 Floor Plan
D11號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D12 D12號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D12 Floor Plan
D12號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D15 D15號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D15 Floor Plan
D15號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D16 D16號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D16 Floor Plan
D16號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D17 D17號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4150, 4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D17 Floor Plan
D17號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D18 D18號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D18 Floor Plan
D18號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖

Upper Roof Plan
上層天台平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D19 D19號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 4425, 4525, 4700, 4800	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D19 Floor Plan
D19號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D20 D20號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200, 5275	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D20 Floor Plan
D20號洋房 樓面平面圖







Upper Roof Plan
上層天台平面圖

B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D21 D21號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D21 Floor Plan
D21號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D22 D22號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D22 Floor Plan
D22號洋房 樓面平面圖



Upper Roof Plan
上層天台平面圖

B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D23 D23號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D23 Floor Plan
D23號洋房 樓面平面圖







Upper Roof Plan
上層天台平面圖

B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D25 D25號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D25 Floor Plan
D25號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D26 D26號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D26 Floor Plan
D26號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖



G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D27 D27號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D27 Floor Plan
D27號洋房 樓面平面圖



B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖



1/F Floor Plan
1樓平面圖



Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	House Number 洋房編號	B1/F 地庫1樓	G/F 地下	1/F 1樓	Roof 天台	Upper Roof 上層天台
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	House D28 D28號洋房	200	150 175, 200	150, 175, 200	200, 225	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)		4550	3925, 3950, 4200	3500, 3750, 3775	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

House D28 Floor Plan
D28號洋房 樓面平面圖



Upper Roof Plan
上層天台平面圖

B1/F Floor Plan
地庫1樓平面圖

G/F Floor Plan
地下平面圖

1/F Floor Plan
1樓平面圖

Roof Plan
天台平面圖

Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位				
			A	B	C	D	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 1 第1座	G/F 地下	150, 175	150, 175	150, 175	150, 200	150, 200
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3500, 3850	3150, 3500, 3850	3500	3500, 3850	3500

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.
4. The "Common Area for Drainage Pipe" and the "Common Fence Wall" do not form part of a residential property and are common parts of the Development. Eligible persons shall have a right of access over such parts or areas. For details, please refer to the latest draft deed of mutual covenant incorporating a management agreement.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。
4. 公共水渠範圍及公共圍牆並不構成住宅物業的一部分，為發展項目的公用地方。有資格人士有權出入該等部分或範圍。詳情請參閱發展項目的公共契約及管理協議的最新擬稿。

Tower 1 G/F Floor Plan
第1座 地下樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位				
			A	B	C	D	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 1 第1座	1/F 1樓	150, 175	150, 175	150, 175	150, 175	150,175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3150	3150	3150	3150	3150

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 1
第1座

1/F Floor Plan
1樓樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 1 第1座	2/F - 3/F, 5/F - 8/F 2樓至3樓，5樓至8樓	150, 175	150, 175	150, 175	150, 175	150, 175	150,175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3150	3150	3150	3150	3150	3150
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 1 第1座	9/F 9樓	150, 175	150, 175	150, 175	150, 175	150, 175	150,175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3500	3500	3500	3500	3500	3500
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 1 第1座	10/F 10樓	150, 175	150, 175	150, 175	150, 175	150, 175	150,175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 1 2/F-3/F, 5/F-10/F Floor Plan
第1座 2樓至3樓、5樓至10樓樓面平面圖





Part Plan for Flat E 2/F
2樓E單位局部平面圖

Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 1 第1座	Roof 天台	150	150	150	150	150	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			N/A	N/A	N/A	N/A	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 1 Roof Plan
第1座 天台樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位				
			B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 2 第2座	G/F 地下	150	150	150	150	150, 200
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3500, 3850	3500	3500	3500, 3850	3150, 3500, 3850

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.
4. The "Common Area for Drainage Pipe" and the "Common Fence Wall" do not form part of a residential property and are common parts of the Development. Eligible persons shall have a right of access over such parts or areas. For details, please refer to the latest draft deed of mutual covenant incorporating a management agreement.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。
4. 公共水渠範圍及公共圍牆並不構成住宅物業的一部分，為發展項目的公用地方。有資格人士有權出入該等部分或範圍。詳情請參閱發展項目的公共契約及管理協議的最新擬稿。

Tower 2 G/F Floor Plan
第2座 地下樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位				
			B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 2 第2座	1/F 1樓	150	150, 175	150, 175	150	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3150	3150	3150	2800, 2850, 3150, 3200	3150

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 2 1/F Floor Plan
第2座 1樓樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 2 第2座	2/F 2樓	150	150	150, 175	150, 175	150	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3150	3150	3150	3150	3150, 3500	3150, 3500
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 2 第2座	3/F, 5/F - 8/F 3樓，5樓至8樓	150	150	150, 175	150, 175	150	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3150	3150	3150	3150	3150	3,150
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 2 第2座	9/F 9樓	150	150	150, 175	150, 175	150	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3500	3500	3500	3500	3500	3500
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 2 第2座	10/F 10樓	150	150	150, 175	150, 175	150	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 2 2/F-3/F, 5/F-10/F Floor Plan
第2座 2樓至3樓、5樓至10樓樓面平面圖



Part Plan of Unit E on 2/F of Tower 2
第2座2樓E單位之局部平面圖



Part Plan of Unit A on 2/F
2樓A單位之局部平面圖

Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 2 第2座	Roof 天台	150	150	150	150	150	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			N/A	N/A	N/A	N/A	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 2 Roof Plan
第2座 天台樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			B	C	D	E	F	G
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 3 第3座	G/F 地下	150, 175	150	150	150	150	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3500, 3850	3500, 3850	3500	3500	3500, 3850	3500, 3850

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.
4. The "Common Area for Drainage Pipe" and the "Common Fence Wall" do not form part of a residential property and are common parts of the Development. Eligible persons shall have a right of access over such parts or areas. For details, please refer to the latest draft deed of mutual covenant incorporating a management agreement.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。
4. 公共水渠範圍及公共圍牆並不構成住宅物業的一部分，為發展項目的公用地方。有資格人士有權出入該等部分或範圍。詳情請參閱發展項目的公共契約及管理協議的最新擬稿。

Tower 3 G/F Floor Plan
第3座 地下樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			B	C	D	E	F	G
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 3 第3座	1/F 1樓	150, 175	150, 175	150, 175	150, 175	150	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3150	3150	3150	3150	3150	3150, 3500

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 3 1/F Floor Plan
第3座 1樓樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位						
			A	B	C	D	E	F	G
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 3 第3座	2/F - 3/F, 5/F - 8/F 2樓至3樓，5樓至8樓	150, 175	150, 175	150, 175	150, 175	150, 175	150	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3150	3150	3150	3150	3150	3150	3150
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 3 第3座	9/F 9樓	150, 175	150, 175	150, 175	150, 175	150, 175	150	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3150, 3225, 3500, 3850	3500	3500	3500	3500	3500	3225, 3500, 3850

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 3 2/F-3/F, 5/F-9/F Floor Plan
第3座 2樓至3樓、5樓至9樓樓面平面圖



Part Plan for Flat A 2/F
2樓A單位局部平面圖

Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 3 第3座	10/F 10樓	125, 150, 175	150, 175	150, 175	150, 175	150, 175	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			3400, 3675, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 3 10/F Floor Plan
第3座 10樓樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 3 第3座	Roof 天台	150	150	150	150	150	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)			N/A	N/A	N/A	N/A	N/A	N/A

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 3 Roof Plan
第3座 天台樓面平面圖



Upper Roof Plan
上層天台平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位			
			B	C	D	E
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 5 第5座	G/F 地下	150	150	150	150
	Tower 5A 第5A座			150	150	150
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 5 第5座		3500	3500	3500	3500, 3850
	Tower 5A 第5A座			3500	3500	3500

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 5 &5A　　G/F Floor Plan
第5及5A座　　地下樓面平面圖



Scale : 0M/米　　5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位				
			A	B	C	D	E
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 5 第5座	1/F 1樓	150	150, 175	150, 175	150, 175	150
	Tower 5A 第5A座		150		150	150, 175	150, 175
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 5 第5座		2800, 3150	3150	3150	3150	3150
	Tower 5A 第5A座		3150		3150	3150	3150

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 5 &5A　1/F Floor Plan
第5及5A座　1樓樓面平面圖



Scale : 0M/米　5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 5 第5座	2/F - 3/F, 5/F - 8/F 2樓至3樓，5樓至8樓	150, 175	150, 175	150, 175	150, 175	150	150, 175
	Tower 5A 第5A座		150, 175	150, 175	150	150, 175	150, 175	
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 5 第5座		3150	3150	3150	3150	3150	3150
	Tower 5A 第5A座		3150	3150	3150	3150	3150	
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 5 第5座	9/F 9樓	150, 175	150, 175	150, 175	150, 175	150	150, 175
	Tower 5A 第5A座		150, 175	150, 175	150	150, 175	150, 175	
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 5 第5座		3500	3500	3500	3500	3500	3500
	Tower 5A 第5A座		3150, 3200, 3500, 3850	3150, 3200, 3500, 3550, 3850	3500	3500	3500	

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 5 &5A 2/F-3/F, 5/F-9/F Floor Plan
第5及5A座 2樓至3樓、5樓至9樓樓面平面圖





Part Plan for Flat B 2/F
2樓B單位局部平面圖



Part Plan for Flat F 2/F
2樓F單位局部平面圖

Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 5 第5座	10/F 10樓	150, 175	150, 175	150, 175	150, 175	150	150, 175
	Tower 5A 第5A座		125, 150, 175		150	150, 175	150, 175	
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 5 第5座		3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750
	Tower 5A 第5A座		3400, 3675, 3700, 3750		3400, 3750	3400, 3750	3400, 3750	

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 5 &5A 10/F Floor Plan
第5及5A座 10樓樓面平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位					
			A	B	C	D	E	F
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 5 第5座	Roof 天台	150	150	150	150	150	150
	Tower 5A 第5A座		150		150	150	150	
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 5 第5座		N/A	N/A	N/A	N/A	N/A	N/A
	Tower 5A 第5A座		N/A		N/A	N/A	N/A	

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 5 &5A Roof Plan
第5及5A座 天台樓面平面圖



Upper Roof Plan
上層天台平面圖



Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位						
			A	B	C	D	E	F	G
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 6 第6座	G/F 地下	150, 200	150,200		200	150	150	150
	Tower 6A 第6A座				150, 200	150, 200	150, 200		
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 6 第6座		3500, 3850	3500, 3850		3500	3500	3500	3500
	Tower 6A 第6A座				3500, 3850	3500	3500		

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.
4. The "Common Area for Drainage Pipe" and the "Common Fence Wall" do not form part of a residential property and are common parts of the Development. Eligible persons shall have a right of access over such parts or areas. For details, please refer to the latest draft deed of mutual covenant incorporating a management agreement.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。
4. 公共水渠範圍及公共圍牆並不構成住宅物業的一部分，為發展項目的公用地方。有資格人士有權出入該等部分或範圍。詳情請參閱發展項目的公共契約及管理協議的最新擬稿。

Tower 6 &6A　G/F Floor Plan
第6及6A座　地下樓面平面圖



Scale : 0M/米　5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位						
			A	B	C	D	E	F	G
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 6 第6座	1/F 1樓	150, 175	150, 175		150, 175	150, 175	150, 175	150, 175
	Tower 6A 第6A座			150, 200	150, 175	150, 175	150, 175		
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 6 第6座		3150	3150		3150	3150	3150	3150
	Tower 6A 第6A座			2800, 3150, 3500	3150	3150	3150		

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 6 &6A 1/F Floor Plan
第6及6A座 1樓樓面平面圖

Scale : 0M/米 5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位						
			A	B	C	D	E	F	G
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 6 第6座	2/F - 3/F, 5/F - 8/F 2樓至3樓，5樓至8樓	150, 175	150, 175	150, 175	150, 175	150, 175	150, 175	150, 175
	Tower 6A 第6A座		150, 175	150, 175	150, 175	150, 175	150, 175		
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 6 第6座		3150	3150	3150	3150	3150	3150	3150
	Tower 6A 第6A座		3150	3150	3150	3150	3150		
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 6 第6座	9/F 9樓	150, 175	150, 175	150, 175	150, 175	150, 175	150, 175	150, 175
	Tower 6A 第6A座		150, 175	150, 175	150, 175	150, 175	150, 175		
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 6 第6座		3150, 3200, 3500, 3550, 3850	3150, 3200, 3500, 3850	3500	3500	3500	3500	3500
	Tower 6A 第6A座		3500	3500	3500	3500	3500		

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 6 &6A 2/F-3/F, 5/F-9/F Floor Plan
第6及6A座 2樓至3樓、5樓至9樓樓面平面圖

Part Plan for Flat C 2/F
2樓C單位局部平面圖



Part Plan for Flat A 2/F
2樓A單位局部平面圖



	Tower Name 大廈名稱	Floor 樓層	Units 單位						
			A	B	C	D	E	F	G
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 6 第6座	10/F 10樓	125, 150, 175		150, 175	150, 175	150, 175	150, 175	150, 175
	Tower 6A 第6A座		150, 175	150, 175	150, 175	150, 175	150, 175		
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 6 第6座		3400, 3750		3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750
	Tower 6A 第6A座		3400, 3750	3400, 3750	3400, 3750	3400, 3750	3400, 3750		

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 6 &6A　　10/F Floor Plan
第6及6A座　　10樓樓面平面圖

Scale : 0M/米　5M/米
比例

	Tower Name 大廈名稱	Floor 樓層	Units 單位						
			A	B	C	D	E	F	G
The thickness of the floor slabs (excluding plaster) of each residential property (mm) 每個住宅物業的樓板(不包括灰泥)的厚度(毫米)	Tower 6 第6座	Roof 天台	150		150	150	150	150	150
	Tower 6A 第6A座		150	150	150	150	150		
The floor-to-floor height (i.e. the height between the top surface of the structural slab of a floor and the top surface of the structural slab of its immediate upper floor) of each residential property (mm) 每個住宅物業的層與層之間的高度(指該樓層之石屎地台面與上一層石屎地台面之高度距離)(毫米)	Tower 6 第6座		N/A		N/A	N/A	N/A	N/A	N/A
	Tower 6A 第6A座		N/A	N/A	N/A	N/A	N/A		

1. The internal areas of the residential properties on the upper floors will generally be slightly larger than those on the lower floors because of the reducing thickness of the structural walls on the upper floors.
   因住宅物業的較高樓層的結構牆的厚度遞減，較高樓層的內部面積，一般比較低樓層的內部面積稍大。
2. The dimensions in the floor plans are all structural dimensions in millimetre.
   樓面平面圖所列之尺寸為以毫米標示之建築結構尺寸。

Notes :

1. According to Special Condition No.(10)(g)(i) of the Land Grant, the total number of residential units in the Development shall not be less than 460 and shall not be more than 480.
2. Clause 45 of the Third Schedule to the latest draft deed of mutual covenant incorporating a management agreement in respect of the Development provides as follows:-

   "Restrictions on the number of Residential Units

   No Owner shall carry out or permit or suffer to be carried out any works in connection with any Residential Unit, including, but not limited to demolition or alteration of any partition wall or any floor or roof slab or any partition structure, which will result in such Residential Unit being internally linked to and accessible from any adjoining or adjacent Residential Unit."
3. A total number of 460 residential units are provided in the Development.

備註：

1. 根據批地文件特別條款第(10)(g)(i)條，發展項目住宅單位總數最少為460個、最多為480個。
2. 發展項目的公共契約及管理協議的最新擬稿的附表3第 45 條有以下條款:

   「限制住宅單位的數目

   每名業主不得進行或允許或容受進行任何與任何住宅單位有關連而會導致該住宅單位與任何毗鄰或毗連住宅單位內部相通及可從任何毗鄰或毗連住宅單位到達的工程，包括但不限於任何間隔牆、任何地板或天花板或任何間隔牆構建物的拆卸或改動。」
3. 發展項目總共提供460個住宅單位。

Tower 6 &6A Roof Plan
第6及6A座 天台樓面平面圖



Upper Roof Plan
上層天台平面圖

Tower 6
第6座



Tower 6A
第6A座



Tower 6A
第6A座

Tower 6
第6座

Scale : 0M/米 5M/米
比例

Description of Residential Property 物業的描述 / House Number 洋房編號	Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)								
		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
House A A號洋房	267.966 (2884) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	26.536 (286)	161.263 (1736)	-	36.207 (390)	4.893 (53)	-	-
House B1 B1號洋房	230.568 (2482) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	19.498 (210)	67.221 (724)	-	31.455 (339)	4.703 (51)	-	-
House B2 B2號洋房	230.733 (2484) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	19.498 (210)	62.499 (673)	-	31.455 (339)	4.703 (51)	-	-
House B3 B3號洋房	230.562 (2482) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	19.498 (210)	60.903 (656)	-	31.455 (339)	4.703 (51)	-	-
House B5 B5號洋房	231.695 (2494) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	19.498 (210)	64.952 (699)	-	31.455 (339)	4.703 (51)	-	-
House B6 B6號洋房	232.251 (2500) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	19.498 (210)	65.607 (706)	-	31.455 (339)	4.703 (51)	-	-
House B7 B7號洋房	231.584 (2493) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	19.498 (210)	61.441 (661)	-	31.455 (339)	4.703 (51)	-	-
House B8 B8號洋房	230.983 (2486) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	19.498 (210)	65.036 (700)	-	31.455 (339)	4.703 (51)	-	-
House B9 B9號洋房	230.427 (2480) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	19.498 (210)	117.476 (1265)	-	31.455 (339)	4.703 (51)	-	-
House C1 C1號洋房	189.426 (2039) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	155.948 (1679)	-	54.305 (585)	4.892 (53)	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述	Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)								
House Number 洋房編號		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
House C2 C2號洋房	188.931 (2034) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	72.769 (783)	-	54.305 (585)	4.892 (53)	-	-
House C3 C3號洋房	189.343 (2038) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	91.846 (989)	-	54.305 (585)	4.892 (53)	-	-
House C5 C5號洋房	189.343 (2038) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	85.985 (926)	-	54.305 (585)	4.892 (53)	-	-
House C6 C6號洋房	189.343 (2038) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	75.166 (809)	-	54.305 (585)	4.892 (53)	-	-
House C7 C7號洋房	188.931 (2034) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	58.436 (629)	-	54.305 (585)	4.892 (53)	-	-
House C8 C8號洋房	188.931 (2034) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	67.742 (729)	-	54.305 (585)	4.892 (53)	-	-
House C9 C9號洋房	188.931 (2034) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	76.181 (820)	-	54.305 (585)	4.892 (53)	-	-
House C10 C10號洋房	188.931 (2034) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	77.406 (833)	-	54.305 (585)	4.892 (53)	-	-
House C11 C11號洋房	189.549 (2040) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	74.947 (807)	-	54.305 (585)	4.892 (53)	-	-
House C12 C12號洋房	189.549 (2040) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	、	-	-	-	63.232 (681)	-	54.305 (585)	4.892 (53)	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述	Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)								
House Number 洋房編號		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
House C15 C15號洋房	191.488 (2061) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	68.073 (733)	-	54.305 (585)	4.892 (53)	-	-
House C16 C16號洋房	191.488 (2061) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	68.370 (736)	-	54.305 (585)	4.892 (53)	-	-
House C17 C17號洋房	191.488 (2061) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	75.507 (813)	-	54.305 (585)	4.892 (53)	-	-
House C18 C18號洋房	191.488 (2061) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	76.345 (822)	-	54.305 (585)	4.892 (53)	-	-
House C19 C19號洋房	191.488 (2061) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	77.328 (832)	-	54.305 (585)	4.892 (53)	-	-
House C20 C20號洋房	188.734 (2032) 露台 Balcony: 3.920 (42) 工作平台 Utility Platform: --	-	-	-	-	48.877 (526)	-	58.253 (627)	4.893 (53)	-	-
House C21 C21號洋房	187.492 (2018) 露台 Balcony: 3.920 (42) 工作平台 Utility Platform: --	-	-	-	-	109.272 (1176)	-	58.253 (627)	4.893 (53)	-	-
House C22 C22號洋房	188.931 (2034) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	72.789 (784)	-	54.305 (585)	4.892 (53)	-	-
House C23 C23號洋房	188.931 (2034) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	72.834 (784)	-	54.305 (585)	4.892 (53)	-	-
House C25 C25號洋房	188.931 (2034) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	72.834 (784)	-	54.305 (585)	4.892 (53)	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述	Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)								
House Number 洋房編號		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
House C26 C26號洋房	189.549 (2040) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	81.386 (876)	-	54.305 (585)	4.892 (53)	-	-
House C27 C27號洋房	189.549 (2040) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	81.386 (876)	-	54.305 (585)	4.892 (53)	-	-
House C28 C28號洋房	189.549 (2040) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	81.386 (876)	-	54.305 (585)	4.892 (53)	-	-
House C29 C29號洋房	189.549 (2040) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	81.386 (876)	-	54.305 (585)	4.892 (53)	-	-
House C30 C30號洋房	189.549 (2040) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	87.581 (943)	-	54.305 (585)	4.892 (53)	-	-
House C31 C31號洋房	195.047 (2099) 露台 Balcony: 3.317 (36) 工作平台 Utility Platform: --	-	-	-	-	77.794 (837)	-	54.305 (585)	4.892 (53)	-	-
House D1 D1號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	82.524 (888)	-	43.180 (465)	4.892 (53)	-	-
House D2 D2號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	70.226 (756)	-	43.180 (465)	4.892 (53)	-	-
House D3 D3號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	66.720 (718)	-	43.180 (465)	4.892 (53)	-	-
House D5 D5號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	76.361 (822)	-	43.180 (465)	4.892 (53)	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述	Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)								
House Number 洋房編號		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
House D6 D6號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	40.683 (438)	-	43.180 (465)	4.892 (53)	-	-
House D7 D7號洋房	165.877 (1786) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	76.242 (821)	-	43.180 (465)	4.892 (53)	-	-
House D8 D8號洋房	165.795 (1785) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	77.998 (840)	-	43.180 (465)	4.892 (53)	-	-
House D9 D9號洋房	165.960 (1786) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	74.001 (797)	-	43.180 (465)	4.892 (53)	-	-
House D10 D10號洋房	165.960 (1786) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	76.617 (825)	-	43.180 (465)	4.892 (53)	-	-
House D11 D11號洋房	166.537 (1793) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	65.352 (703)	-	43.180 (465)	4.892 (53)	-	-
House D12 D12號洋房	166.207 (1789) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	86.472 (931)	-	43.180 (465)	4.892 (53)	-	-
House D15 D15號洋房	166.042 (1787) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	82.244 (885)	-	43.180 (465)	4.892 (53)	-	-
House D16 D16號洋房	165.877 (1786) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	76.758 (826)	-	43.180 (465)	4.892 (53)	-	-
House D17 D17號洋房	165.209 (1778) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	79.615 (857)	-	43.180 (465)	4.892 (53)	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述	Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
House Number 洋房編號		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
House D18 D18號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	95.568 (1029)	-	43.180 (465)	4.892 (53)	-	-
House D19 D19號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	63.438 (683)	-	43.180 (465)	4.892 (53)	-	-
House D20 D20號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	63.046 (679)	-	43.180 (465)	4.892 (53)	-	-
House D21 D21號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	63.482 (683)	-	43.180 (465)	4.892 (53)	-	-
House D22 D22號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	63.469 (683)	-	43.180 (465)	4.892 (53)	-	-
House D23 D23號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	63.489 (683)	-	43.180 (465)	4.892 (53)	-	-
House D25 D25號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	63.477 (683)	-	43.180 (465)	4.892 (53)	-	-
House D26 D26號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	63.466 (683)	-	43.180 (465)	4.892 (53)	-	-
House D27 D27號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	63.453 (683)	-	43.180 (465)	4.892 (53)	-	-
House D28 D28號洋房	163.815 (1763) 露台 Balcony: 3.631 (39) 工作平台 Utility Platform: --	-	-	-	5.998 (65)	49.129 (529)	-	43.180 (465)	4.892 (53)	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 1 第1座	G/F 地下	A	73.391 (790) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	9.918 (107)	-	-	-	-	-
		B	74.839 (806) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	22.379 (241)	-	-	-	-	-
		C	75.307 (811) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	22.379 (241)	-	-	-	-	-
		D	43.028 (463) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	13.129 (141)	-	-	-	-	-
		F	42.977 (463) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.743 (169)	-	-	-	-	-
	1/F 1樓	A	75.334 (811) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	1.915 (21)	-	-	-	-	-	-
		B	75.735 (815) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		C	77.151 (830) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	44.641 (481) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		F	44.978 (484) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 1 第1座	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	76.857 (827) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.504 (16)	-	-	-	-	-	-	-	-	-	-
		B	76.828 (827) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		C	77.151 (830) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	44.488 (479) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	42.944 (462) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		F	44.129 (475) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
	10/F 10樓	A	76.857 (827) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.504 (16)	-	-	-	-	-	-	66.479 (716)	-	-	-
		B	76.828 (827) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	60.964 (656)	-	-	-
		C	77.151 (830) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	60.842 (655)	-	-	-
		D	44.488 (479) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	43.205 (465)	-	-	-
		E	42.944 (462) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	36.104 (389)	-	-	-
		F	44.129 (475) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	35.659 (384)	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 2 第2座	G/F 地下	B	45.143 (486) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	12.844 (138)	-	-	-	-	-
		C	41.293 (444) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.578 (168)	-	-	-	-	-
		D	41.294 (444) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.578 (168)	-	-	-	-	-
		E	48.116 (518) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	12.288 (132)	-	-	-	-	-
		F	52.213 (562) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	13.110 (141)	-	-	-	-	-
	1/F 1樓	B	47.144 (507) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		C	43.294 (466) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		D	43.295 (466) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	50.117 (539) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		F	53.594 (577) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 2 第2座	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	43.652 (470) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		B	47.144 (507) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		C	43.294 (466) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		D	43.295 (466) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	47.559 (512) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		F	53.198 (573) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
	10/F 10樓	A	43.652 (470) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	42.075 (453)	-	-	-
		B	47.144 (507) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	38.783 (417)	-	-	-
		C	43.294 (466) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	36.071 (388)	-	-	-
		D	43.295 (466) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	37.675 (406)	-	-	-
		E	47.559 (512) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	33.524 (361)	-	-	-
		F	53.198 (573) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	40.359 (434)	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 3 第3座	G/F 地下	B	45.294 (488) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	16.466 (177)	-	-	-	-	-
		C	45.887 (494) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	12.899 (139)	-	-	-	-	-
		D	42.792 (461) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.463 (166)	-	-	-	-	-
		E	40.582 (437) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	17.213 (185)	-	-	-	-	-
		F	44.373 (478) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	9.763 (105)	-	-	-	-	-
		G	46.376 (499) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.293 (165)	-	-	-	-	-
	1/F 1樓	B	47.295 (509) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		C	47.792 (514) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	42.709 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	42.709 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		F	46.276 (498) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		G	64.572 (695) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 3 第3座	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	69.431 (747) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		B	47.127 (507) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		C	47.792 (514) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	42.709 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	42.709 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		F	46.276 (498) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		G	48.178 (519) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 3 第3座	10/F 10樓	A	115.500 (1243) 露台 Balcony: 3.003 (32) 工作平台 Utility Platform: --	-	-	-	-	-	-	92.974 (1001)	5.130 (55)	-	-
		B	47.127 (507) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	37.204 (400)	-	-	-
		C	47.792 (514) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	38.222 (411)	-	-	-
		D	42.709 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	35.568 (383)	-	-	-
		E	42.709 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	35.568 (383)	-	-	-
		F	46.898 (505) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	40.610 (437)	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 5 第5座	G/F 地下	B	40.841 (440) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.642 (168)	-	-	-	-	-
		C	42.158 (454) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.640 (168)	-	-	-	-	-
		D	49.744 (535) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	18.171 (196)	-	-	-	-	-
		E	48.456 (522) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	16.096 (173)	-	-	-	-	-
	1/F 1樓	A	76.021 (818) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		B	42.842 (461) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		C	44.159 (475) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		D	51.855 (558) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		E	50.347 (542) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 5 第5座	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	75.615 (814) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		B	42.842 (461) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		C	44.159 (475) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		D	51.855 (558) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		E	50.347 (542) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		F	50.787 (547) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
	10/F 10樓	A	75.615 (814) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	56.104 (604)	-	-	-
		B	42.842 (461) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	34.581 (372)	-	-	-
		C	44.159 (475) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	36.691 (395)	-	-	-
		D	51.855 (558) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	41.471 (446)	-	-	-
		E	50.347 (542) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	40.663 (438)	-	-	-
		F	50.787 (547) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	36.572 (394)	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 5A 第5A座	G/F 地下	C	43.411 (467) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.640 (168)	-	-	-	-	-
		D	40.585 (437) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.640 (168)	-	-	-	-	-
		E	40.652 (438) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.278 (164)	-	-	-	-	-
	1/F 1樓	A	72.550 (781) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		C	48.667 (524) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	42.586 (458) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	42.653 (459) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 5A 第5A座	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	72.358 (779) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		B	75.854 (816) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		C	48.667 (524) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	42.586 (458) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	42.653 (459) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
	10/F 10樓	A	124.451 (1340) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	17.383 (187)	-	-	107.697 (1159)	4.320 (47)	-	-
		C	48.667 (524) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	31.879 (343)	-	-	-
		D	42.586 (458) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	39.291 (423)	-	-	-
		E	42.653 (459) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	35.721 (385)	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 6 第6座	G/F 地下	A	74.048 (797) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	28.521 (307)	-	-	-	-	-
		B	75.393 (812) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	28.521 (307)	-	-	-	-	-
		D	76.297 (821) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	21.929 (236)	-	-	-	-	-
		E	41.503 (447) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.753 (170)	-	-	-	-	-
		F	42.066 (453) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.754 (170)	-	-	-	-	-
		G	45.756 (493) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	16.239 (175)	-	-	-	-	-
	1/F 1樓	A	76.852 (827) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		B	78.197 (842) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	79.101 (851) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		E	43.504 (468) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		F	44.067 (474) 露台 Balcony:2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		G	47.757 (514) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 6 第6座	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	76.852 (827) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		B	77.927 (839) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		C	77.605 (835) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		D	78.906 (849) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		E	43.504 (468) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		F	44.067 (474) 露台 Balcony:2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		G	47.757 (514) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 6 第6座	10/F 10樓	A	125.766 (1354) 露台 Balcony: 4.047 (44) 工作平台 Utility Platform: --	-	-	-	20.611 (222)	-	-	104.660 (1127)	6.837 (74)	-	-
		C	77.605 (835) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	66.390 (715)	-	-	-
		D	78.906 (849) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	62.460 (672)	-	-	-
		E	43.504 (468) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	36.397 (392)	-	-	-
		F	44.067 (474) 露台 Balcony:2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	36.843 (397)	-	-	-
		G	47.657 (513) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	38.719 (417)	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

AREA OF RESIDENTIAL PROPERTIES IN THE DEVELOPMENT
發展項目中的住宅物業的面積

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 6A 第6A座	G/F 地下	C	45.006 (484) 露台 Balcony: -- 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	12.288 (132)	-	-	-	-	-
		D	40.726 (438) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.754 (170)	-	-	-	-	-
		E	40.760 (439) 露台 Balcony: -- 工作平台 Utility Platform: --	-	-	-	-	15.642 (168)	-	-	-	-	-
	1/F 1樓	B	52.850 (569) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	26.835 (289)	-	-	-	-	-	-
		C	49.835 (536) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	42.727 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	42.761 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

Description of Residential Property 物業的描述			Saleable Area (including balcony, utility platform and verandah, if any) sq. metre (sq. ft.) 實用面積 (包括露台，工作平台及陽台(如有))平方米(平方呎)	Area of other specified items (Not included in the Saleable Area) sq. metre (sq. ft.) 其他指明項目的面積(不計算入實用面積) 平方米(平方呎)									
Block Name 大廈名稱	Floor 樓層	Unit 單位		Air-conditioning plant room 空調機房	Bay window 窗台	Cockloft 閣樓	Flat roof 平台	Garden 花園	Parking space 停車位	Roof 天台	Stairhood 梯屋	Terrace 前庭	Yard 庭院
Tower 6A 第6A座	2/F - 3/F, 5/F - 9/F 2樓至3樓，5樓至9樓	A	75.125 (809) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		B	54.181 (583) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		C	49.835 (536) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	-	-	-	-
		D	42.727 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
		E	42.761 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	-	-	-	-
	10/F 10樓	A	75.125 (809) 露台 Balcony: 2.804 (30) 工作平台 Utility Platform: --	-	-	-	-	-	-	60.346 (650)	-	-	-
		B	54.181 (583) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	45.902 (494)	-	-	-
		C	49.835 (536) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: 1.5 (16)	-	-	-	-	-	-	31.470 (339)	-	-	-
		D	42.727 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	36.340 (391)	-	-	-
		E	42.761 (460) 露台 Balcony: 2.001 (22) 工作平台 Utility Platform: --	-	-	-	-	-	-	34.794 (375)	-	-	-

Notes:

1. The saleable area and the floor areas of balcony, utility platform and verandah (if any) are calculated in accordance with section 8 of the Residential Properties (First-hand Sales) Ordinance; and the areas of other specified items (not included in the saleable area) are calculated in accordance with Part 2 of Schedule 2 to the Residential Properties (First-hand Sales) Ordinance.
2. The above areas have been converted to square feet based on a conversion rate of 1 square metre=10.764 square feet and rounded off to the nearest integer.

附註:

1. 實用面積以及露台、工作平台及陽台(如有)之樓面面積，是按照《一手住宅物業銷售條例》第8條計算得出的。其他指明項目(不計算入實用面積)的面積，是按照《一手住宅物業銷售條例》附表2第2部計算得出的。
2. 上述所列之面積以1平方米 = 10.764平方呎換算至平方呎，並四捨五入至整數。

FLOOR PLANS OF PARKING SPACES IN THE DEVELOPMENT
發展項目中的停車位的樓面平面圖

B1/F 地庫1樓 Zone A A區

Key Plan
索引圖



- Residential Parking Space
  住客停車位
- Accessible Residential Parking Space
  暢通易達住客停車位
- Visitors' Parking Space
  訪客停車位
- Accessible Visitors' Parking Space
  暢通易達訪客停車位
- Residential Motor Cycle Parking Space
  住客電單車停車位
- Bicycle Parking Space
  單車停車位
- Refuse Collection Vehicle Parking Space
  垃圾車停車位
- Boundary of the Development
  發展項目的界線

Scale : 0M/米 10M/米 20M/米
比例

FLOOR PLANS OF PARKING SPACES IN THE DEVELOPMENT
發展項目中的停車位的樓面平面圖

B1/F 地庫1樓

Zone B B區

Key Plan 索引圖



Residential Parking Space
住客停車位

Boundary of the Development
發展項目的界線

Scale : 0M/米 10M/米 20M/米
比例

FLOOR PLANS OF PARKING SPACES IN THE DEVELOPMENT
發展項目中的停車位的樓面平面圖

G/F
地下

Zone C
C區

Key Plan
索引圖



Residential Loading and Unloading Space
住客上落貨停車位

Boundary of the Development
發展項目的界線

Scale : 0M/米 10M/米 20M/米
比例

Numbers, Dimensions and Areas of Parking Spaces
停車位數目、尺寸及面積

Floor 樓層	Category of Parking Spaces 停車位類別	Parking Space Number 停車位編號	Number 數目	Dimensions (L x W) (m) 尺寸 (長x 闊) (米)	Area of Each Parking Space (sq. m) 每個停車位面積 (平方米)
G/F 地下	Residential Loading and Unloading Space 住客上落貨停車位	L/UL 1 - L/UL 5	5	11 x 3.5	38.5
B1/F 地庫1樓	Residential Parking Space 住客停車位	R001 - R002, R004 - R031, R033- R035, R037 - R170	167	5 x 2.5	12.5
	Accessible Residential Parking Space 暢通易達住客停車位	R003 , R032 , R036	3	5 x 3.7	18.5
	Visitors' Parking Space 訪客停車位	V001 - V003, V005 - V016	15	5 x 2.5	12.5
	Accessible Visitors' Parking Space 暢通易達訪客停車位	V004	1	5 x 3.7	18.5
	Bicycle Parking Space 單車停車位	B01 - B20	20	1.7 x 0.4	0.68
	Residential Motor Cycle Parking Space 住客電單車停車位	M01 - M11	11	2.4 x 1	2.4
	Refuse Collection Vehicle Parking Space 垃圾車停車位	RCV	1	12 x 5	60

1. A preliminary deposit of 5% of the purchase price is payable on the signing of the preliminary agreement for sale and purchase (the "preliminary agreement");
2. The preliminary deposit paid by the purchaser on the signing of the preliminary agreement will be held by a firm of solicitors acting for the owner, as stakeholders;
3. If the purchaser fails to execute the agreement for sale and purchase within 5 working days after the date on which the purchaser enters into the preliminary agreement-
   (i) that preliminary agreement is terminated;
   (ii) the preliminary deposit is forfeited; and
   (iii) the owner does not have any further claim against the purchaser for the failure.

1. 在簽署臨時買賣合約(「該臨時合約」)時須支付款額為售價之5%的臨時訂金；
2 買方在簽署該臨時合約時支付的臨時訂金，會由代表擁有人行事的律師事務所以保證金保存人的身份持有；
3. 如買方沒有於訂立該臨時合約的日期之後5個工作日內簽立買賣合約-
   (i) 該臨時合約即告終止；
   (ii) 有關的臨時訂金即予沒收；及
   (iii) 擁有人不得就買方沒有簽立買賣合約而針對買方提出進一步申索。